Construction Specifications

BUILDER

Sterling Land Company 1037 Hinesburg Rd, Suite A South Burlington, VT 05403

HOME OWNER

DESCRIPTION

Brook Plan: two story home with unfinished lower level. Two floors of finished area with approximately 1,584 square feet of living space; 816 square feet of unfinished Lower Level, 400 square foot 2-car garage, 48 square foot front porch.

SPECIFICATIONS INDEX

Section 1: Permits Section 2: Structural Detail and Exterior Selections Section 3: Electrical Rough In Details and Specifications Section 4: Lighting Plumbing Section 5: Fireplace and Mantle Cabinets & Countertops Section 6: Section 7:

Section 8: Wall & Trim Interior Detail Work Section 9: Flooring and Paint Selections Section 10: Appliances Section 11: Landscaping Section 12: Site Work and Preparation Section 13: Miscellaneous

REVISIONS

PERMITS

C/O Number

C/O code C/O Date Plan Date

PERMITS: Builder responsible to obtain all necessary permits including.

Building permits

STRUCTURE DETAIL & EXTERIOR SELECTIONS

FOUNDATIONS/LOWER LEVEL:

Poured Concrete Type: Wall Height: 7-10" Lookout Height: 4' Frost Wall Min. 3000 PSI @ 28 days with steel reinforcement Continuous 8" x 24" Reinforced Strength: Footer: Damp proofing applied below grade Sealer:

FLAT WORK CONCRETE: Lower Level: Poured concrete

-0	ower Level: Poured concrete.			
	Finish	Smooth		
	"Keyway" joints:	Saw Cut		
	Thickness:	4"		
	Strength:	House: Min. 3000 PSI @ 28 days		
		Garage: Min. 4000 PSI @ 28 days		
	Moisture Barrier:	Tarred damp proofing coating sprayed on exterior of foundation walls.		
		6 mil poly under concrete house slab.		
	Ground water controls:	Stone and perforated drain tile pipe on outside drained to daylight		

FRAME:

Exterior walls:	2x6 SPF 24" o.c.
Interior walls:	2x4 SPF 24" o.c.
Plate height:	9'-1" on first floor, 8'-1" on the second floor, and 7'-10" in Lower Level.
Plate:	2x6 treated Southern Yellow Pine with foam sill seal.
Floor Framing:	2x10 SPF 19.2" o.c.
Sub Flooring:	³ ⁄4" 4x8 T&G OSB glued and nailed.
Girders:	2 or 3 ply 2x12, nailed and glued, as specified by engineering load
	design, supported by 3-1/2" concrete filled lally columns in Lower Level
Sheathing:	7/16" 4x8 OSB
Roof:	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting
	Pitches: 6/12 and 5/12 at Main House; 5/12 at Garage; 5/12 at Front Porch
House wrap:	Professional house wrap with flashing around all windows and doors.
Misc. Framing Details:	None

1 of 10 Smokebush F Base Spec 6-21-18

Brook Plan 6/26/2018 Brook Plan **Specifications Date:** 6/28/2018

PROJECT ADDRESS Smokebush Lane

Essex, VT 05452

Plan:

Plan Date:

Specifications:

ROOFING:

ROOFING:	Owens Corning TruDefinition Duration shingles. Ice and water shield on eaves and valleys.
Shingles: Color:	Vented on ridge to achieve proper ventilation. Owens Corning TruDefinition Duration Limited Lifetime Warrantee Onyx Black
SIDING:	
	Norandex "Woodsman Select"
Gable Ends:	Vinyl Shakes, Color to "Champagne"
Clapboard:	Double 4" Color to be "Champagne"
Board-and-Baton:	None.
Eaves:	Two piece aluminum wrapped-White
	10" Frieze Board under eaves at front of House and Garage
Soffit:	Perforated Soffit for proper venting
Corners:	6" Vinyl Corners with Foam Backer
Trim details:	Frieze board and Garage Door trim to be Miratech
Drip Edge:	Galvanized
Gutters & downspouts.	White Seamless gutters

WINDOWS:

Brand:	Jeld-Wen New Construction Double Hung Window
Construction:	All- Vinyl, energy star qualified, argon-filled, low-E insulated double-pane windows.
	Maximum U-factor .28. Brickmould exterior casing with built-in J and nailing flange
	EZ-Tilt cleaning. Screens included. Properly flashed.
Grills:	Grills Between Glass 6 over 0
Screens:	Fiberglass mesh.

Window Schedule

LETTER	LOCATION	SIZE	TYPE	QTY.	NOTES
Α	Dining Room	3465	Dbl. Hung	2	
A2	Living Room	6875	Dbl. Hung	1	
В	Den/ Master BR, BR #2/3	3453	Dbl. Hung	6	
B2	Den	6853	Dbl. Hung	1	
С	Master Bath	3442	Dbl. Hung	1	
D	Bath #2	2626	Awning	1	
E	Master BR, BR #2, BR #3	3453	Casement	3	
EG	Lower Level	5548	Slider	1	
G	Lower Level	3624	Awning	1	
K	Kitchen	3649	Dbl. Hung	1	

EXTERIOR DOORS:

Brand: Construction:

Therma-Tru Insulated Fiberglass Doors Insulated fiberglass exterior doors with full weather stripping and adjustable sills. 6-9/16" jambs w/ 5/4x4 exterior trim. All exterior doors to have deadbolt locks. Door knobs and deadbolts keyed alike. All locksets/deadbolts to be EZ-Set satin nickel finish. A "jam-sill" weather pan will be installed at the threshold of all exterior doors with the exception of the garage to mudroom door.

Screen Doors:

Door Schedule

None

LOCATION	SIZE	TYPE	QTY.	HARDWARE	
					l
1st Fl. Foyer LH	3' - 0"	6 Panel	1	Double Bore	
S210 6 Panel with S210 Sidelite knob side					
Mudroom to Garage LH	3' - 0"	2 panel	1	Double Bore	
S220 2 panel Panel Solid					
Living Room to Back Yard RH	3' - 0"	2 Panel	1	Double Bore	
S118 Full Glass No Grilles					
	1st Fl. Foyer LH S210 6 Panel with S210 Sidelit Mudroom to Garage LH S220 2 panel Panel Solid Living Room to Back Yard RH	1st Fl. Foyer LH 3' - 0" S210 6 Panel with S210 Sidelite knob side Mudroom to Garage LH 3' - 0" S220 2 panel Panel Solid Living Room to Back Yard RH 3' - 0"	1st Fl. Foyer LH 3' - 0" 6 Panel S210 6 Panel with S210 Sidelite knob side Mudroom to Garage LH 3' - 0" 2 panel S220 2 panel Panel Solid Living Room to Back Yard RH 3' - 0" 2 Panel	1st Fl. Foyer LH 3' - 0" 6 Panel 1 S210 6 Panel with S210 Sidelite knob side Mudroom to Garage LH 3' - 0" 2 panel 1 S220 2 panel Panel Solid Living Room to Back Yard RH 3' - 0" 2 Panel 1	1st Fl. Foyer LH 3' - 0" 6 Panel 1 Double Bore S210 6 Panel with S210 Sidelite knob side Mudroom to Garage LH 3' - 0" 2 panel 1 Double Bore S220 2 panel Panel Solid Living Room to Back Yard RH 3' - 0" 2 Panel 1 Double Bore







Entry Door I

Mudroom to Garage II

Back Yard III

OVERHEAD GARAGE DOOR:

Door: Design: Color: Car Opener: Insulated 16' x 7' Garage Door Contemporary Flat Panel To match siding color, "Champange" Yes - 2 8" Lift master 1/2 Horsepower Electric opener Keyless Entry Punch Pad included



YA

DECKS & PORCHES

Porch Framing:	6' x 8' Front Porch framed with PT 2x8 joists and 5/4x6 PT decking. Miratech wrapped and painted PT 6x6 square posts. Posts wrapped on top and bottom. Roof to be truss framed. Roof shingles to match house. Porch ceiling to be vinyl bead board. Stairs from porch to walkway will be PT Box Stairs with 5/4x6 PT treads.
Porch Finish	Porch deck, Stairs, Risers, and Rimboard to be stained with TWP Total Wood Preservative, Color To Be TWP Dark Oak 1503 Porch Posts and Beams to be White
Rear Deck	Available as an Option
Rear Deck Finish	
Rear Deck Railing:	Color: N/A

ELECTRICAL & LOW VOLTAGE:

Plugs/Switches: Switches/Plugs Switch Style Plate Style Switch Color Dimmers Dimmer Style Dimmer Color Dimmer Locations	Underground service, 150 AMP panel. Toggle White Available as an Option	tł.
Exterior plugs	Per Electrical Plan	
Lighting: Lighting fixtures: Recessed lights	See Lighting section.	
Miscellaneous Electrical: Door chime Smoke/CO detectors Bath vents	Nutone: One 2-note, white door chime, Model BK125LWH 1 CO per floor (3 total), 1 Smoke per bedroom (3 total) Included, Master Bath & Bath #2 to have 110cfm fan/light with programmable controls Powder Room to have 50cfm fan with on/off switch	
Security System Central Vacuum CAT 5 (data/phone) TV Jacks: Audio:	None. No. Yes, per electrical plan Yes, per electrical plan No.	S.

ELECTRICAL ROUGH IN DETAILS AND SPECIFICATIONS

LIGHTING

PLUMBING

LIGHT FIXTURES: Dining Room KIC 43651AP Garage Exterior KIC 9618OZ Foyer Island KIC 43655AP KIC 43654AP Bath #2 Vanity Master Vanity/Powder Room Living Room Master Bed KIC 5336CH Maxim Ž681FTSN Maxim 2681FTSN KIC 5337CH Laundry/Master Closet KIC 209WH





Future Deck KIC 96110Z



Upstairs Hall/Mudroom/Guest Bedrooms Maxim 2680MRSN



Yes No

Yes

Yes Yes, 1st floor

GAS-PROPANE Main Kitchen Range Main Fireplace Furnace Hot water system Dryer

HEATING Boiler Brand:

Boiler Size: Efficiency Rating: Zones: Air Conditioner: Thermostat: Bath venting: Dryer venting

York LX Series, TM9V 40,000 BTU 96.0% One zone, 1st and 2nd floor Available as option 1 thermostat per zone (1 zone) Bath fans Per plan.

PLUMBING FIXTURES:

Kitchen:

Sink Model:

Description: Color: Size: Strainers:

Faucet Model: Description: Color: Option:

Disposal Model: 11401-3-NA Sterling South Haven Double Bowl Top-Mount Sink Stainless Steel 32" L x 22" W x 7" deep Dearborn Stainless Basket Strainer

K-596-CP Kohler Simplice with Spray Polished Chrome Metal Strainers

Available as Option



Master Bath:

2 Faucets Model: Description: Color:

Shower Model: Description: Color: Shower Rod:

Shower Trim Model: Description: Color:

Toilet Model: Description: Size: Color:

Bath #2:

Faucet Model: Description: Color:

Tub/ Shower Model: Description: Color:

Tub/ Shower Trim Model: Description: Color:

Toilet Model:

Description: Size: Color:

Powder Room: (1/2 Bath)

Faucet Model:

Description: Color:

Pedestal Model: Description: Color: Dimensions:

Toilet Model: Description: Size: Color: Kohler Refinia Lavatory Faucet Polished Chrome

K-5316-4-CP

S-60

Aker Alcove Shower White Straight curtain rod (installed)

K-TS5320-4E-CP Kohler Refinia w/2.0 gpm showerhead Polished Chrome

21-912 Gerber Maxwell Standard Heigh elongated bowl toilet 28 1/2"L x 17 1/2"W x 29"H White

K-5316-4-CP Kohler Refinia Lavatory Faucet Polished Chrome

GB-60 Aker Alcove tub/shower White

K-TS5318-4E-CP Kohler Refinia w/2.0 gpm showerhead Polished Chrome

21-912 Gerber Maxwell Standard Heigh elongated bowl toilet 28 1/2"L x 17 1/2"W x 29"H White

K-5316-4-CP Kohler Refinia Lavatory Faucet Polished Chrome

Gerber Model 22-514 Maxwell 4" Center Standard Pedestal White 25 1/2" x 20 1/2" x 34"

21-912 Gerber Maxwell Standard Heigh elongated bowl toilet 28 1/2"L x 17 1/2"W x 29"H White





















Miscellaneous Plumbing

Outdoor Faucets: Hot Water Heater: Laundry: 2 Frost-Free Hose Bibs, located at back of the main house and one on the right side of the front porch. State 50 gallon electric water heater Washer Box Valve with single handle shutoff Laundry appliances pricing optional

PVC drainage plumbing. PEX continuous piping for all domestic water. All plumbing installed according to National Plumbing Code by licensed plumber.

Radon piping runs from under Lower Level concrete slab through roof. This is a passive system, no fan.

FIREPLACE & MANTLE

FIREPLACE:

Model:

Mantle:

Tile Surround:

Color:

Venting:

CABINETS & COUNTERTOPS

CABINETS:

All kitchen, bath, and built-in cabinet features: Kitchen Cabinets to be Mid Continent Pro Series

All kitchen cabinets are Bayfield style in Stained Oak, color to be "Natural" Bath Vanity Cabinets to be Mid Continent Pro Series Bath Vanities to be Bayfield style in Stained Oak, color to be "Natural"

Available as an Option

Cabinet plans are drawn and presented to the client before cabinet construction begins. **Photos are meant to show cabinet style only, actual color may vary

CABINET NOTES:

None

All cabinet pulls/knobs Amerock BP 53005-G10 Kitchen Pulls Bathroom Knobs Amerock BP 53005-G10



53005

COUNTERTOPS:

Location: Style: Color: Edge Detail: Cut-Outs: Backsplash: B/S Location:

Location: Style: Color: Edge Detail:

Location: Style: Color: Edge Detail: Cut-Outs: Backsplash: B/S Location:

Location: Style: Color: Edge Detail: Cut-Outs: Backsplash: B/S Location: Kitchen Surround Laminate To Be Selected by Owner E-2000 Self-rimming sink. Yes Back only.

Kitchen Island Granite - Builders Series To Be Selected by Owner Pencil Edge

Master Bathroom 60" vanity Cultured Marble with integrated bowls White with White Bowls Square Edge None Yes Back only.

Bath #2 48" vanity Cultured Marble with integrated bowl White with White Bowl Square Edge None Yes Back only.





Vanities

Kitchen



Kitchen Tops (not color, but style)



Master Bath Top



Bath #2 Top (1 Bowl)

WALL & TRIM INTERIOR DETAIL WORK

INSULATION:

Type:	NGBS Standard
Exterior walls:	R-21- 6" Fiberglass Batts with Poly Vapor Barrier
Interior Walls:	R-13- 3-1/2" Fiberglass Batts for bath walls (soundproofing)
Spray Foam:	Box sill in first and second floor joists insulated with closed cell foam.
Attic:	R-60 Cellulose with backer boards at eaves for ventilation.
Garage:	Not insulated.
Foundation:	2-1/2" R-15 Thermax glued to concrete wall.

DRYWALL:

Living area walls:	1/2" sheet rock, taped with 3 coats of joint compound at walls and ceilings
Ceilings:	Smooth Finish, minor shadow variations are possible in ceilings.
Garage:	5/8" sheetrock taped with 1 coat joint compound at walls and ceilings

INTERIOR TRIM: "Colonial"

INTERIOR TRIM: "Colonia	al"		1 1
Casing:	2-1/2" Colonial Casing		
Base:	3-1/2" Colonial Base Board		
<u>Interior doors:</u> Make: Model: Color: Hinges:	Masonite Smooth 2 Panel Hollow Core To Be Selected by Owner Satin Nickel		
Door Knobs:	5		
Exterior: EZ-Set Ke	eyed Entry w/deadbolt Satin Nickel		
Interior: EZ-Set Sa	atin Nickel	A CO	
<u>Other:</u> Satin Nickel handrail bra	ackets, hinge bumps and base bumps.		
<u>Stairs:</u> Main Level to Second Floor Lower Level to Main Level: <u>Mirrors and Glass:</u>	r: Carpet Grade Carpet Grade		
Mirrors: Location: Master Bath Bath #2 Powder	Details: Plate Glass mirror with ground edge, no Plate Glass mirror with ground edge, no By Owner		
Shower Curtain Rods	Bath #2 + Master Bath	Straight Rod.	

Wainscot/wall treatment:

Crown:

Built-Ins:

Bath Hardware: <u>Item:</u> Toilet Paper Holder Towel Ring 24" Towel Bar Robe Hook <u>ltem #:</u> K-37054 K-37057 K-37051 K-37055

Available as an option

Available as an option

Quantity:

Mudroom

<u>Finish:</u> Polished Chrome Polished Chrome Polished Chrome Polished Chrome

Coat Pegs



CLOSET SHELVING: All closet systems will be vented wire and the system, per the picture here, is indicated on the plan. This includes the pantry.

Master WIC:	2 Shelf and Rod
Master Reach-In:	1 Shelf and Rod
Master Linen:	4 Shelf
Bedroom 2:	1 Shelf and Rod
Bedroom 3:	1 Shelf and Rod
Mudroom:	1 Shelf and Rod

FLOORING AND PAINT SELECTIONS

FLOORING:

Wood Floors Location Make:	Foyer, Dining Room, Kitchen BSL
Style:	Horizon Grade Maple
Finish:	Natural Finish 4 1/4" width

Carpet

aipot				
Location:	Living Room, Den, Master B	R & WIC, BR 2 & 3, Stai	irs, and Upstairs Hallway	
Make:	Shaw	Color:	To Be Selected by Owner	
Style:	Turn the Page	Details:		

Luxury Vinyl

Location: Maker: Style:

Mudroom, Mudroom Closet, Laundry, Powder Mannington LVS Size Gold Weight Colo Size: Color:

To be selected from: Unique, Slate, Stone, or Wood

Vinyl Loca

ocation:	Bath #2 and Master Bath
Make:	Mannington
Style:	Jumpstart
Color:	To Be Selected by Owner

PAINT:

Exterior Paint:

Exterior Doors:	2 coats of Glidden exterior paint, Front Door Color To Be selected by owner.	
Overhead Door:	To match siding color "Champagne"	
Exterior Lap Siding:	D-4 Vinyl Siding, Not Painted	
Trim :	Including freeze boards, doo Color: Finish:	r surrounds Glidden White Satin finish
Windows:	Manufacturer's White	
Front Porch:	Porch Decking, Steps, and Rimboard to be stained with TWP Total Wood Preservative, Color to be Dark Oak, 1503. Porch Posts and Roof Beams to be White.	
Rear Deck:	N/A	



Interior Paint:	Paint plan will be developed and approved as selections are made.	
Painted Interior Walls:	1 coat primer with 2 coats of Pittsburgh Paints flat latex paint, Color To Be Low VOC Interior paint to be used	
Accent Wall Color:	Available as an option	
Ceilings:	To Match Walls	
Interior Trim, painted:	Painted, 1 primer coat, 2 coats of Pittsburgh Paints semi-gloss latex paint Color: To Match Sherwin Williams "High Reflective White" SW7757	
Interior Doors:	Color:	To Match Sherwin Williams "High Reflective White" SW7757
Interior Trim, stained:	Semi-Gloss finish N/A	

APPLIANCES

APPLIANCES:

<u>Kitchen</u>

Refrigerator Whirlpool Make: Model: WRS335SDHB Color: Black Side-by-side Features:

Gas Range

Make: Whirlpool Model: WFG515S0EB Color: Black Features: Self Cleaning Oven

Dishwasher Make: Model:

Color:

Whirlpool WDF540PADB Black Features:

Microwave Make:

Model: Color:

Whirlpool WMH31017HB Black Features: Located over Range. Location:

Available as an option

Laundry

Washer Model Color Details

Dryer Model

Color

Available as an option Details

1







LANDSCAPING:

All disturbed portions of yard to be seeded. Lawn area will generally include front yard, side yard, and rear yard to the tree line. Lawn area to be covered with approximately 4" of native topsoil. Landscaping of this home includes 6 deciduous shrubs, 2 evergreen shrubs, 8 perennials, and 1 deciduous tree.

SITE WORK AND PREPARATION

SITE CLEARING:

Builder is responsible for all site clearing, as needed.

EXCAVATION & FILL:

Builder responsible for all site work and site balance to include:

- Connection to Town of Essex water
- * Connection to community septic with leach field
- Connection to propane gas tank. Underground power, telephone and cable TV in conduit to house
- 12" thick gravel two car driveway on top of mirafi fabric. Driveway to be finished paved with 2" of compacted asphalt.
- Footing drains installed around Lower Level and drained to daylight in back yard. Drain tile buried in clean 1" stone;
- covered with mirafi fabric; clean sand fill from fabric to 12" below grade. Site graded to shed surface water away from house.
- Boulder rock walls as needed for the grading of the yard. Boulders from the site are machine-placed to create walls.
- Sidewalk from front porch to driveway will be Hollandstone paver bricks: color is red.
- Yards, shrubs, landscaping, snow and trash removal are the responsibility of the Homeowners Assosciation. Owner can plant additional plantings around their home.

MISCELLANEOUS

CLEANING:

House cleaned prior to closing, including washing of windows.

ENERGY PACKAGE:

Home to be built to Vermont Energy Code. Options to be presented for VIEC 2.0 and the National Green Building Standard. Home to include:

- 110 CFM fan to exhaust air from the house in Master Bath and Bath #2, controlled by a programmable 24-hour timer. 1)
- Programmable setback thermostat 2)
- 3) Additional caulking and sealing of joists to reduce air infiltration into the home, including shoe plate; windows; and where wires and pipes go to cold spaces.
- Lower Level insulation on the interior using rigid "Thermax" insulation to be located from the floor to the top 4) of concrete wall
- Selected use of closed cell foam to improve overall air sealing of home. 5)
- 6) Pre-drywall and diagnostic testing after the house is complete by Efficiency VT

WARRANTY: SCI Warrantee as per contract.

Continuing a policy of constant research and improvement, Sterling Land Company reserves the right to make substitutions and specification changes.

SIGNATURES:

Client:

Date

Date

Client:

Collin Frisbie, Builder

Date