

WENTWORTH GL HOME - CONSTRUCTION SPECIFICATIONS

Builder Clearview Properties, LLC 1037 Hinesburg Road, Suite A South Burlington, VT 05403 Homeowner/Project

Clearview #52

Specification Date: 7/12/2021 Site Plan Date: 6/22/2021 Plan Date: 6/28/2021

Wentworth Plan: One story home with unfinished lower level. Approximately 1,490 square feet of living space; 1,490 square feet of unfinished Lower Level, 462 square foot 2-car garage, and a 54 square foot front porch.

Location Total Square Feet First Floor 1,490

Total Finished Square Feet 1,490
Lower Level 1,490
Garage 462
Front Porch 54

Front Porch **Personal Choice Lists** PCL# **Color Code Date GRAPE ORANGE** GOLD **GREEN BLUE PURPLE PINK RUST HUNTER SKY BLUE LAVENDER BROWN NAVY** LIME **CRANBERRY AQUA PEACH** RED

Specification and Appendix Approval

Appendix A: Window Schedule
Appendix B: Exterior and Interior Door Schedule
Appendix C: Lighting Schedule
Appendix D: Plumbing Schedule
Appendix E: Finish Hardware Schedule
Appendix F: Flooring Schedule
Appendix G: Appliance Schedule

Client		Date
Client		Date
Builder	C.W. Fried	D-1-
Builder	Collin Frisbie	Date



Section	Information	Imaga
mits	Information	Image
mits	Builder responsible to obtain all necessary permits including:	
	- Soil Erosion and Sediment Control	
nyoye.	- Zoning	
veys		
	Home is to be staked by builder	
e Clearing		
	Builder is responsible for all site clearing, as needed	
lities Connections		
	Builder responsible for all site work and site balance to include	
Water	Connection to City of Milton water system	
Sewer	Connection to City of Milton sewer system	
Gas	Connection to Natural Gas lines at road.	
Power	Underground power	
Cable	Cable TV conduit to house	
	All excavation, fill and labor is included	
ergy Package		
	Home to be built to VT Residential Building Energy Standards (RBES)	
	Compliant with Act 250 Stretch Code	
Home to Include	Compliant With the 250 Street Code	
nome to metade	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
	Vented to the outside	
	Additional caulking and air sealing of joists to reduce air infiltration into the home, including	
	shoe plate; windows; and where wires and pipes go to cold spaces	
	R-15 Rigid Thermax insulation on Interior of Lower Level - floor to top of concrete wall	
	Selected use of closed cell foam to improve overall air sealing of attic in home	
	Blower Door Test as home completed required for VT RBES	
Solar Prep	Home solar ready with conduit running from LL up to Attic Space	
undation		
Type	Poured Concrete	
Wall Height	8'	
Lookout Height	4' Frost Wall	
Strength	Min. 3000 PSI @2 days with steel reinforcement	
Footer	Continuous 8" x 16" reinforced	
t Work Concrete		
Lower Level	Poured Concrete	
Finish	Smooth	
"Keyway" Joints	Saw cut	
Thickness	4"	
Strength	House: Min. 3000 PSI @ 28 days Garage: Min. 4000 PSI @ 28 days	
	Tarred damp proofing membrane sprayed on exterior of foundation walls.	
Moisture Barrier	6 mil poly under concrete house slab.	
	Footing drains installed below footers around Lower Level and drained to daylight in back yard.	
Ground water controls	Drain tile buried in clean stone; covered with mirafi fabric; clean sand fill against foundation. Site	
	graded to shed surface water away from house.	
	Boulder rock walls as needed for the grading of the yard.	
Rock Wall	Boulders from the site are machine-placed to create walls.	
Deck Prep	3 Concrete Piers included for future deck	
veway/Entrance	5 contracts Field included for future deak	
Total a grant a market	12" thick gravel two car driveway on top of mirafi fabric.	
Drive	Driveway to be finish paved with 2" of compacted asphalt.	
	Driveway to be fiffish paved with 2 of compacted asphalt.	The state of the s
Walkway	42" Sidewalk from front porch to driveway	



-		
Frame	2 C CDF 24II	
Exterior Walls	2x6 SPF 24" o.c.	
Interior Walls	2x4 SPF 24" o.c.	
Plate Height	9'-1" on first floor; 8'-1" on second floor and 8' in lower level	
Plate	2x6 treated southern yellow pine with foam sill seal	
Floor Framing	2x10 SPF 19.2" o.c.	
Sub Flooring	3/4" 4x8 T&G OSB glued and nailed	
Girders	2 or 3 ply 2x12, nailed and glued, as specified by engineering load design, supported by 3-1/2"	
	concrete filled lally columns in Lower Level	
Sheathing	7/16" 4x8 OSB	
Roof	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting	
Roof Pitch	Pitches: 8/12 at Main House; 8/12 at Front Porch; 5/12 at front of Garage; 6/12 at Garage taper;	
Nooi Fitch	6/12 at rear of Garage	
House Wrap	Professional house wrap with flashing around all windows and doors	
Roofing		
	Ice and water shield on eaves and valleys. Vented on ridge to achieve proper ventilation.	
Underlayment	Owens Corning ProArmor Synthetic Roof Underlayment	and the state of t
Shingles	Owens Corning TruDefinition Shingles Limited Lifetime Warranty	
Color	Onyx Black	
Siding/Exterior Elements		
Siding	Norandex Woodsman Select	
Gable Ends	Vinyl Shakes, Color to be Sandstone	
Clapboard	Double 4", Color to be Sandstone	
Board and Baton	None	
Eaves	Two piece aluminum wrapped - White	
Soffit	Perforated soffit for proper venting	
Corners	6" White Vinyl Corners with Foam Backer	
Trim Details	Frieze board and Garage Door Trim to be PVC	Sandstone
Drip Edge	Galvanized	
Shutters	Available as Option	
Gutters & Downspouts	Available as Option	
Gutters & Downspouts	White Seamless Gutters	
Windows	White Scanness Gatters	
TVIII dows	See Appendix A: Window Schedule	
Brand	Harvey Slimline	
Color	White	
Construction	Vinyl, Low-E, Insulated Double-Pane	
Exterior Casing	J Channel Only (Brickmould)	
U-Factor	0.30 Grills Between Glass 6 over 0	
Grills		
Screens Exterior Doors	Fiberglass Mesh	
Exterior Doors	Con Annuality By Estavior and Interior Dear Schoolule	
Due of	See Appendix B: Exterior and Interior Door Schedule Therma-Tru	
Brand		
Color	See Exterior Paint Section	
Construction	Insulated Fiberglass	
Exterior Casing	5/4x4 Flat	
Storm Doors	None	
Overhead Garage Doors	0200 Codes Insulated Steel Deep	
Model	8300 Series Insulated Steel Door	
Size	16' x 7'	
Design	Colonial Raised Panel Door	
Color	Manufacturer White	
Opener	8" lift master 1/2 horsepower electric opener	
Remotes	2 remotes included	
Frame Key Pad	Keyless entry punch pad	



Decks & Porches		
Covered Entry Porch		
Porch Framing	6' x 9' framed with PT 2x8 joists	
Decking	5/4x6 PT decking	
Decking	374XOTT GEGING	
Posts	PVC wrapped and PT 6x6 Posts, 2x8 roof beams - White. Posts wrapped top and bottom.	
5 (
Roof	Roof to be truss framed, roof shingles to match house	
Ceiling	White vinyl bead board	
Stairs	Stairs from porch to walkway to be PT box steps with 5/4x6 PT treads.	
Rail	Pressure treated rail and balusters	
Finish	Porch posts, beams, PT rim board and stair risers	
Color	Porch decking and stair tread stained with Total Wood Preservative - Color to be Dark Oak	
Future Deck	14' x 12' Deck Available as Option	
Deck Prep	Ledger Board and 3 Concrete Piers included for future deck	
Exterior Paint		
Exterior Doors - Excluding Front Door	Painted Satin Finish, White	
Exterior Trim - Including Frieze Board and Door Surrounds	Painted Satin Finish, White	Backwoods CC-630
Front Door	2 coats Exterior Paint, Color to be BM CC-630 Backwoods, OK to Color Match	
Sidelight	Painted Satin Finish, Color to be BM CC-630 Backwoods, OK to Color Match - INCUDING WINDOW TRIM	
Front Porch Rail	Pressure Treated - painted white	
Front Porch Posts	Painted White	
Front Porch Roof Beams	Painted White	
Front Porch Rim board	Stained. Color to be Selected by Owner.	
Front Porch Stair Risers	Stained. Color to be Selected by Owner.	
Front Porch Decking	Stained. Color to be Selected by Owner.	
Electrical & Low Voltage	Stained. Color to be selected by Owner.	
Liectrical & Low Voltage	Underground electrical service, 40 circuit 150 AMP Panel with Surge Protection. Open double	
	slot for future solar.	
Plugs and Switches		
Switch Style	Toggle	•
Plate Style	Toggle screw on plates	
Switch Color	White	50
Dimmers	Available as Option	e i
Exterior Plugs	Per Electrical Plan	Φ
Lighting		
Lighting Fixtures	See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	
Recessed Lights	13 Click Lights: Kitchen 4, Front Porch 2, Main Hallway 3, Mudroom 2, Hall to Owner's Bedroom 2	
Under Cabinet Lighting	Available as Option	
Miscellaneous		
	GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished	
Outlets	areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.	
Door Chime	Nutone BK125LWH: One 2-note, white door chime	
	1 CO/Smoke per floor (1 Total), 1 Smoke per bedroom (2 Total) - Kidde 120V Intelligent 10 Year	
Smoke/CO2	Lithium Battery Smoke Alarm Model P4010ACS	
Bath Vents	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM	
Paddle Fan Boxes	Paddle fan rated boxes in all Bedrooms, Dining room, and Living room	
Cat 5 (data/phone)	Yes, per electrical plan	
TV Jacks	Yes, per electrical plan	
Security/Surveillance	None	
Central Vacuum	None	
Audio	None	
Solar Prep	Conduit running from LL up to Attic Space	
Garbage Disposal	Available as Option	
Light Fixtures	ηναιιανίε αδ Ομιίοι	
LIGHT FIXCUICS	See Appendix C: Light Fixture Schedule	
	See Appendix C. Light Fixture Schedule	



	Plumbing	
Heating and Venting		
Furnace	York LX Series, TM9V	
Furnace Size	40,000 BTU	
Efficiency Rating	96%	
Zones	Zone 1: First Floor	72
Second Zone	Available as Option	
Air Conditioner	Available as Option	0.000
Thermostat	Ecobee Thermostat; First Floor	
Bath Venting	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light. Vented to the outside	
Dryer Venting	Microwave/Hood Vent vented to the outside	
Gas		
Main Kitchen Range	Yes	
Main Fireplace	Available as Option	
Floor Dryer	No	
Furnace	Yes	
Hot Water System	Yes	
Grill Line at Deck	Available as Option	
Fireplace and Mantle		
Fireplace in Living Room	Available as Option	
Model		
Mantle		
Tile Surround		
Tile Hearth		
Venting		
Plumbing Fixtures		
Adi	See Appendix D: Plumbing Schedule	
Miscellaneous Plumbing		
Outdoor Faucets	2 Frost-Free Hose Bibs, located at back of the main house and on the side of the front porch	
Hot Water Heater	Rinnai R-75 LSI On Demand Water Heater	
Laundry	Washer Box Valve with single handle shutoff and drain; appliances pricing optional	
	PVC Drainage plumbing.	
Plumbing	PEX continuous piping for all domestic water.	
	All plumbing installed according to National Plumbing Code by licensed plumber.	
Radon	Radon Piping runs from under Lower Level concrete slab through roof.	
	This is a passive system, no fan.	
Utility Sink	Available as Option	



	Cabinets & Countertops	
Cabinets		
Kitchen		
Brand	Mid Continent Pivot Series	
Style	Dapper F/O Style in Maple Stain	
Base Color	Thorn	
Style	Dapper F/O Style in Maple Painted White	
Uppers Color	White	
Kitchen Island		
Brand	Mid Continent Pivot Series	
Style	Dapper F/O Style in Maple Stain	
Color	Thorn	
Owner's Bath		
Size	72" Vanity with 2 bowls	
Brand	Mid Continent Pivot Series	Total Control of the
Style	Dapper F/O Style in Maple Stain	
Color	Chestnut	Name of the last o
Bath #2	Criestriut	
	42" Vanitu with single hawl	The state of the s
Size	42" Vanity with single bowl	
Brand	Mid Continent Pivot Series	
Style	Simple F/O Style in Maple Painted	
Color	Thorn	
Countertops		
Kitchen		
Style	Classic Series Quartz	
Color	Miami Vena	
Edge Detail	Pencil Edge	100 10 10
Cut-Outs	Under Mount Sink	
Backsplash	4" Quartz	
B/S Location	Perimeter Back Only	
Kitchen Island		
Style	Classic Series Quartz	
Color	Miami Veba	_
Edge Detail	Pencil Edge	_
Cut-Outs	None	Kitchen Tops (not color or Style)
	Notice	Kitchen Tops (not color of Style)
Owner's Bath	Culture d March In with 2 interrested flush as storyels because	
Style	Cultured Marble with 2 integrated flush rectangle bowls	
Color	Cotton White	Mr
Edge Detail	Square Edge	The state of the s
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
Bath #2		
Style	Cultured Marble with 1 integrated flush rectangle bowls	
Color	Cotton White	
Edge Detail	Square Edge	-
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
·	Wall & Trim Interior Detail Work	
Insulation		
Exterior Walls	R-21 6" Fiberglass Batts with Poly Vapor Barrier	
Interior Walls	R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing)	
Rigid Insulation	Box sill in first and second floor joists insulated with rigid insulation	
Attic	R-60 Cellulose with backer boards at eves for ventilation	
Garage	Not insulated	_
Foundation	2-1/2" R-15 Thermax glued to concrete wall	_
Drywall	12 1/2 It 13 Inclinar graca to concrete wall	1
	1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings	
Living area walls		—
Ceilings	Smooth Finish, minor shadow variations are possible in ceilings	—
Garage	Unfinished	
Trim Details		
Casing	2-1/2" Colonial Casing	
Base	3-1/2" Colonial Base Board	1 3
Wainscot	+/-60" High Wainscot at Mudroom under Black Metal Coat Hooks and behind Bench	
7741113334	Available as Option	



Built - Ins		
Duit - iiis		
	Bench, Coat Hooks, Cubbies in Mudroom	
Mirrors		
Owners Bath	Plate Glass mirror with ground edge, no bevel	
Bath #2	Plate Glass mirror with ground edge, no bevel	
Interior Stairs/Railing		
Main to Lower Level	Carpet Grade Stairs	
	Rail on wall stained	
	Half wall, cap stained to match wood floor	
Handrail Brackets	Satin Nickel	
Closet Shelving		
	All closets systems will be vented wire and the system is indicated on the plan.	
	See Closet Plan for Details.	
Interior Paint		
	1 coat primer	Windle Proth
Painted Interior Walls	2 coats Low VOC Flat Latex Paint, Color to be BM OC-24 Wind's Breath, OK to Color Match	Wind's Breath OC-24
	2 coats low voc riat latex raint, color to be bivi oc-24 wind's breath, ok to color iviator	
Accent Wall	None	
Ceilings	To match walls	
Interior Trim	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
interior friin	Color to be BM OC-65 Chantilly Lace, OK to Color Match	
Wainscot	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	Chantilly Lace
waniscot	Color to be SBM OC-65 Chantilly Lace, OK to Color Match	
Interior Doors	Painted, 2 coats of Semi-Gloss Latex Paint, Color to be BM OC-65 Chantilly Lace, OK to Color	
interior boors	Match	
Fireplace Mantle (optional)		
Main to Lower Level Stairs	Stained railing to Match Wood on First Floor	
Interior Doors		
	See Door Appendix B: Exterior and Interior Door Schedule	
Finish Hardware		
	See Appendix E: Finish Hardware Schedule	
Flooring		
	See Appendix F: Flooring Schedule	
Appliances		
	See Appendix G: Appliance Schedule	
Landscaping		
	All disturbed portions of yard to be seeded.	
Lawn	Lawn area will generally include front yard, side yard and rear yard.	
	Lawn area to be covered with approximately 4" of native topsoil.	
8 Foundation Shrubs	To be Selected by Owner, See Landscape Plan	
8 Perennial Flowers	To be Selected by Owner, See Landscape Plan	
Cleaning		
	House cleaned prior to closing, including washing of windows	
Warranty		
	Clearview Properties, LLC Warranty as per contract	
	Continuing a policy of constant research and improvement, Clearview Properties, LLC reserves	
	the right to make substitutions and specification changes.	
	I .	



Appendix A: Window Schedule

Harvey Slimline All Vinyl Windows, Double insulated, Low E, GBG Grills 6 over 0 6 9/16 primed interior jambs, 2 1/2 colonial case interior

10 1 (B: 1 11)

J Channel Only (Brickmould)

EZ-Tilt cleaning

Screens included

Energy Star Qualified

Maximum U Factor 0.30

Letter	Size	Quantity	Description	Location	Image	Notes
А	34x65	7	Double Hung	Dining Room, Bedroom 2		
В	34x53	4		Owners Bedroom, Bedroom 2		
С	34x42	1	Double Hung	Owner Bath		
К	42x49	1	Double Hung	Kitchen		
G	36x24	1	Concrete Hopper	Lower Level		
EG	55x48	2	Egress	Lower Level		
	1					



Appendix B: Exterior and Interior Door Schedule EXTERIOR DOORS

Therma-Tru Smooth Star Fiberglass Exterior Doors with full weather stripping and adjustable sills

Grills between glass

6 9/16 primed jambs

Base Bumps

Hinge Bumps

10

10

	Quantity	Description	Opens	Size	Туре	Hardware	lmage	Notes
oyer Entry								
	1	S220 2 panel with S210SL Sidelite	LH	3'-0" - 6'8"	2 Panel	Double Bore		
arage Entry								
	1	S220 2 Panel	RH	3'-0" - 6'8"	2 Panel	Double Bore		
ining Room Entry	from Optional Dec	k						
	1	Harvey Vinyl Sliding Patio Door	LH	6'-0" - 6'8"	Slider	Glass		
xterior Door Hard	lware							
Knobs	2	EZ - Set Keyed Entry w/deadbolt				Satin Nickel		All Keyed Alike
	·		IN ⁻	TERIOR DOORS				
Colonial Casing bot Dexter Stratus Sati		ardboard, 4 9/16 PFJ s air included	plit jambs					
nterior Doors								
	10	Masonite Smooth	See Plans - will display more clearly with plans	TBD	2 Panel Hollow Core	Double Bore		
nterior Door Hard	ware							
Knobs	10	EZ - Set				Satin Nickel		

Satin Nickel

Satin Nickel



						П	DIVIES
		Apper	ndix C: Light	Fixture Sched	lule		
	Quantity	Description	SKU	Item	Color	Image	Notes
Garage Exterior						_	
	1	One Light Outdoor Wall Lantern	534299	Maxim 1024PE	Pewter		
Optional Deck Exte	rior						
	1	One Light Outdoor Wall Lantern	967425	Maxim 1025PE	Pewter		
Front Porch							
	2	Click Lights - LED Flush Mount	3636303	Maxim 57641WTWT	White		
Foyer							
	1	Three Light Semi Flush Mount	738584	Kichler 43669NI	Brushed Nickel	9	
Mudroom							
	2	Click Lights - LED Flush Mount	3636303	Maxim 57641WTWT	White		
Main Hallway							
	3	Click Lights - LED Flush Mount	3636303	Maxim 57641WTWT	White		
Kitchen Island							
	2	One Light Mini Pendant	738588	Kichler 43668NI	Brushed Nickel		
Kitchen							
	4	Click Lights - LED Flush Mount	363603	Maxim 57641WTWT	White		



						11.5	J IVI E 3
Dining Room						-	
	1	Five Light Chandelier	738590	Kichler 43665NI	Brushed Nickel	43.05	
Living Room							
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel	*	
Stairwells							
	1	One Light Wall Sconce	738960	Kichler 45568NI	Brushed Nickel	6	Main to Lower Level
Owners Bedroom H	allway						
	2	Click Lights - LED Flush Mount	363603	Maxim 57641WTWT	White		
Owners Bedroom							
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel	*	
Owners Vanity							
·	2	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		
Owners Closet							
	2	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel		



Dodroom #0						
Bedroom #2						
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	
Bath #2						
	1	Three Light Bath	738938	Kichler 45570NI	Brushed Nickel	
Laundry Room						
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	
Other						
Garage, Future Bonus Room, Lower Level	13	PC Lights				Supplied by Electrician



Appendix D: Plumbing Schedule							
	Qty.	Description	Manutacturer	Product No.	Finish	Image	Notes
Kitchen							
Sink	1	32" Undermount 16 Gauge Stainless Steel Double Bowl Kitchen Sink	Krauss	KBU32	Stainless Steel		32" L x 18" W, 8.5"D, (2) Strainers and Grates
Faucet	1	Arbor Single-Handle Pull Down Sprayer	Moen	7594C	Chrome	P	
Owner's Bath							
Faucet	2	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	M	
Shower	1	2 Seat 60" Shower by MAAX	Aker	141029	White	a	Straight Curtain Rod Installed.
Shower Fixture	1	Eva Collection Eco- Performance Trim Kit	Moen	T2138EP	Chrome	9	Moen 2520 Shower Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height
Bath #2					ı		
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	M	
Tub/Shower	1	GB 60" Tub/Shower	Aker Products	141004	White		Straight Curtain Rod Installed.
Tub/Shower Trim	1	Eva Conversion Eco- Performance Tub/Shower Trim	Moen	T2139EP	Chrome		Moen 2520 Shower Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height



Appendix E: Finish Hardware Schedule							
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes
Owner's Bath	Qiy.	Description	Mandacidiei	TTOGOCT NO.	1 11 11 311	illiage	140163
Knob	4	VAILE 1-3/8in(35mm) Length Knob	Amerock	BP53014G10	Satin Nickel	•	
Pull	3	VAILE 3-3/4in(96mm) Center- To-Center Pull	Amerock	BP53003G10	Satin Nickel		
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome		
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome	3	
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome	3	
ath #2							
Knob	1	VAILE 1-3/8in(35mm) Length Knob	Amerock	BP53014G10	Satin Nickel		
Pull	6	VAILE 3-3/4in(96mm) Center- To-Center Pull	Amerock	BP53003G10	Satin Nickel		
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome		
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome	2	
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome		
itchen Surround							
Knob	16	VAILE 1-3/8in(35mm) Length Knob	Amerock	BP53014G10	Satin Nickel		
Pull	2	VAILE 3-3/4in(96mm) Center- To-Center Pull	Amerock	BP53003G10	Satin Nickel		
itchen Island							
Knob	4	VAILE 1-3/8in(35mm) Length Knob	Amerock	BP53014G10	Satin Nickel		
Pull	2	VAILE 3-3/4in(96mm) Center- To-Center Pull	Amerock	BP53003G10	Satin Nickel		



Appendix F: Flooring Schedule

Wood Floors							
Location	Make	Style	Finish	Size		Image	
Foyer, Hallway, Kitchen, Dining Room, Living Room	BSL	Pacific Grade Red Oak	Sierra Nanoshell Finish	3-1/4" Width			
			Tile Flo				
Location	Make/Style	Finish/Color	Tile Size	Orientation	Tile Grout	Image	Notes
Owner's Bath	American Olean	Danya in Cove	10 x 14	50% Stagger	Antique White		
Mudroom	American Olean	Danya in Basin	10 x 14	50% Stagger	Dusty Grey		
	Make	Style	Vinyl Flo Color	oors		Image	Notes
	,,, <u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>	0.7.0	33.01			illiage	110.00
Bath #2	Tarkett	Fresh Start	Travertine Tile in Creamona	Short Edge to the Door	N/A		
Laundry	Tarkett	Fresh Start	Travertine Tile in Creamona	Long Edge to the Door	N/A		
	Make	Style	Carpo Color	et Details		Image	
			2 2 2 2 2	. 5.55			
Owners Bedroom	Dreamweaver	Pinpoint	Champagne Fizz				
Owners WIC	Dreamweaver	Pinpoint	Champagne Fizz				
Den/Bedroom 2	Dreamweaver	Pinpoint	Champagne Fizz				



		Λn	nendiy C. Anal	iance Scho	dula		O WILS
Appendix G: Appliance Schedule							
Appliance	Quantity	Manufacturer	Model	Color	Description	Image	Notes
Kitchen							
Refrigerator	1	GE	GNE27JYMFS	Stainless	GE Energy Star 27.0 Cu. Ft. French Door		Fingerprint Resistant Door
Gas Range	1	GE	JGS760SPSS	Stainless	GE 30" Side-In Convection Gas Range		
Dishwasher	1	GE	GDT530PSPSS	Stainless	GE Dishwasher with Front Controls		
Microwave	1	GE	JVM3160RFSS	Stainless	GE 1.6 Cu. Ft. Over- the-Range- Microwave Oven		
Laundry Room							
Washer							Available as option
Electric Dryer							Available as option