

SPRUCE HOME - CONSTRUCTION SPECIFICATIONS

Builder Clearview Properties, LLC 1037 Hinesburg Road, Suite A South Burlington, VT 05403 Homeowner/Project Model Home Clearview #36 - 415 Horseshoe Circle Milton, VT 05468 Specification Date: 4/10/23 Site Plan Date: Plan Date: Electric Plan Date:

Spruce Plan: Two story home with unfinished lower level. Two floors of finished area with approximately 1,870 square feet of living space; 830 square feet of unfinished Lower Level, 484 square foot 2-car garage and a 180 square foot front porch.

Location	Total Square Feet
First Floor	900
Second Floor	900
Lower Level	70
Total Finished Square Feet	1,800
Lower Level	860
Garage	484
Front Porch	180

FIGHT FOICH		
	Personal Choice Lists	
PCL#	Color Code	Date
Model Upgrades	GRAPE	4/10/2023
	ORANGE	
	GOLD	
	GREEN	
	BLUE	
	PURPLE	
	PINK	
	HUNTER	
	SKY BLUE	
	LAVENDER	
	BROWN	
	NAVY	
	CRANBERRY	
	AQUA	
	PEACH	
	RED	

Specification and Appendix Approval

Appendix A: Window Schedule
Appendix B: Exterior and Interior Door Schedule
Appendix C: Lighting Schedule
Appendix D: Plumbing Schedule
Appendix E: Finish Hardware Schedule
Appendix F: Flooring Schedule

Appendix G: Appliance Schedule

Client		Date
Client		Date
Builder	Collin Frisbie	Date



	SPRUCE HOME - CONSTRUCTION SPECIFICATIONS	
Section	Information	Image
mits		
	Builder responsible to obtain all necessary permits including:	
	- Soil Erosion and Sediment Control	
	- Zoning	
veys		
	Home is to be staked by builder	
e Clearing		
. cicaring	Builder is responsible for all site clearing, as needed	
lities Connections	Builder is responsible for all site clearing, as needed	
nties connections	Builder responsible for all site work and site balance to include	
Water	Connection to City of Milton water system	
Sewer	Connection to City of Milton sewer system	
Gas	Connection to City of Militon sewer system Connection to Natural Gas lines at road.	
Power	Underground power	
Cable	Cable TV conduit to house	
argy Backage	All excavation, fill and labor is included	
ergy Package	Harranta ha huilt ta VT Basidantial Building France, Ctandanda (BBFC)	
	Home to be built to VT Residential Building Energy Standards (RBES)	
	Compliant with Act 250 Stretch Code	
Home to Include	Para and a Million and the TM Face / Links - Oxide Const Mantillation Colletion - 440 CFMA Park Face / Links	
	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
	Vented to the outside	
	Additional caulking and air sealing of joists to reduce air infiltration into the home, including	
	shoe plate; windows; and where wires and pipes go to cold spaces	
	R-15 Rigid Thermax insulation on Interior of Lower Level - floor to top of concrete wall	
	Selected use of closed cell foam to improve overall air sealing of attic in home	
	Blower Door Test as home completed required for VT RBES	
Solar Prep	Home solar ready with conduit running from LL up to Attic Space	
ındation		
Type	Poured Concrete	
Wall Height	8	
Lookout Height	4' Frost Wall	
Strength	Min. 3000 PSI @2 days with steel reinforcement	
Footer	Continuous 8" x 16" reinforced	
t Work Concrete		
Lower Level	Poured Concrete	
Finish	Smooth	
"Keyway" Joints	Saw cut	
Thickness	4"	
Strength	House: Min. 3000 PSI @ 28 days Garage: Min. 4000 PSI @ 28 days	
	Tarred damp proofing membrane sprayed on exterior of foundation walls.	
Moisture Barrier	6 mil poly under concrete house slab.	
	Footing drains installed below footers around Lower Level and drained to daylight in back yard.	
Ground water controls	Drain tile buried in clean stone; covered with mirafi fabric; clean sand fill against foundation. Site	
	graded to shed surface water away from house.	
	Boulder rock walls as needed for the grading of the yard.	
Rock Wall	Boulders from the site are machine-placed to create walls.	
Deck Prep	Yes	
Lower Level Slab Plumb	Yes	
veway/Entrance	I TO TO THE PARTY OF THE PARTY	
veway/ Littlatice	12" thick gravel two car driveway on top of mirafi fabric.	
Drive		
	Driveway to be finish paved with 2" of compacted asphalt.	
		and the same of th



		HOWES
Frame		
Exterior Walls	2x6 SPF 24" o.c.	
Interior Walls	2x4 SPF 24" o.c.	
Plate Height	9'-1" on first floor and 8' in lower level	
Plate	2x6 treated southern yellow pine with foam sill seal	
Floor Framing	2x10 SPF 19.2" o.c.	
Sub Flooring	3/4" 4x8 T&G OSB glued and nailed	
SubTiodinig	2 or 3 ply 2x12, nailed and glued, as specified by engineering load design, supported by 3-1/2"	
Girders		
Chaathing	concrete filled lally columns in Lower Level 7/16" 4x8 OSB	
Sheathing	·	
Roof	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting	
Roof Pitch	Pitches: 8/12 at Main House; 8/12 at Front Porch; 5/12 at front of Garage; 6/12 at Garage taper;	
	6/12 at rear of Garage	
House Wrap	Professional house wrap with flashing around all windows and doors	
Roofing		
	Ice and water shield on eaves and valleys. Vented on ridge to achieve proper ventilation.	
Underlayment	Owens Corning ProArmor Synthetic Roof Underlayment	
Shingles	Owens Corning TruDefinition Shingles Limited Lifetime Warranty	
Color	Onyx Black	
Siding/Exterior Elements		
Siding	Norandex Woodsman Select - Silver	
Gable Ends	Vinyl Shakes, Color to selected by owner - Silver	
Clapboard	Double 4", Color to be selected by owner - Silver	
Board and Baton	None	
Eaves	Two piece aluminum wrapped - White	
Soffit	Perforated soffit for proper venting	
	• • •	
Corners	6" White Vinyl Corners with Foam Backer	Silver
Trim Details	Frieze board and Garage Door Trim to be Miratech	Sitvei
Drip Edge	Galvanized	
Shutters	Available as Option	
Gutters & Downspouts		
Gutters & Downspouts	White Seamless Gutters	
Windows		
	See Appendix A: Window Schedule	
Brand	Harvey Slimline	
Color	White	
Construction	Vinyl, Low-E, Insulated Double-Pane	
Exterior Casing	J Channel Only (Brickmould)	
U-Factor	0.30	
Grills	Grills Between Glass 6 over 0	
Screens	Fiberglass Mesh	
Exterior Doors	, 0	
	See Appendix B: Exterior and Interior Door Schedule	
Brand	Therma-Tru	
Color	See Exterior Paint Section	
Construction	Insulated Fiberglass	
Exterior Casing	5/4x4 Flat	
Storm Doors	None	
Overhead Garage Doors	mone	
Model	8300 Series Insulated Steel Door	
Size	16' x 7'	
Design	Colonial Raised Panel Door	
Color	Manufacturer White	
Opener	8" lift master 1/2 horsepower electric opener	
Remotes	2 remotes included	
Frame Key Pad	Keyless entry punch pad	



ecks & Porches		
Covered Entry Porch		
Porch Framing	6' x 9' framed with PT 2x8 joists	
Decking	5/4x6 PT decking	
Decking	Sy 4xo i i decking	
Posts	Miratech wrapped and PT 6x6 Posts, 2x8 roof beams - White. Posts wrapped top and bottom.	
Roof	Roof to be truss framed, roof shingles to match house	
Ceiling	White vinyl bead board	
Stairs	Stairs from porch to walkway to be PT box steps with 5/4x6 PT treads. Stained Total Wood	
	Preservative - Dark Oak	
Rail	Available as an Option	
Finish	Porch posts, beams - CPVC White	
Color	Porch decking, stair tread, risers and PT Rim stained with Total Wood Preservative - Dark Oak	
Rear Deck	Available as an Option	
xterior Paint		
Exterior Doors - Excluding Front Door	Painted Satin Finish, White	Lush
Exterior Trim - Including Frieze Board and Door Surrounds	Painted Satin Finish, White	AF-475
Front Door	2 coats Exterior Paint, Color to be Lush Benjamin Moore (AF-475)	
Sidelight	Painted Satin Finish, Color to be Lush Benjamin Moore (AF-475)	
Front Porch Rail	Available as an Option	
Front Porch Posts	·	
	CPVC Wrapped - White	The second second
Front Porch Roof Beams	CPVC Trim - White	A RESIDENCE OF THE PARTY OF THE
Front Porch Rim board	Stained. Color to be TWP Dark Oak	
Front Porch Stair Risers	Stained. Color to be TWP Dark Oak	
Front Porch Decking	Stained. Color to be TWP Dark Oak	
lectrical & Low Voltage		
	Underground electrical service, 40 circuit 150 AMP Panel with Surge Protection. Open double	
	slot for future solar.	
Divers and Constables	Siot for future solar.	
Plugs and Switches		
Switch Style	Toggle	•
Plate Style	Toggle screw on plates	
Switch Color	White	Ba.
Dimmers	Available as Option	Ų- ij
Exterior Plugs	Per Electrical Plan	•
Lighting		
	Cool inhting Finish Cahadula (Annandiy Collight Firtures Cahadula)	
Lighting Fixtures	See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	
Recessed Lights	13 Click Lights: Kitchen 4, Front Porch 2, Main Hallway 3, Mudroom 2, Hall to Owner's Bedroom 2	
Under Cabinet Lighting	Available as Option	
Miscellaneous		
Outlets	GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.	
Door Chime	Nutone BK125LWH: One 2-note, white door chime	
Smoke/CO2	1 CO/Smoke per floor (3 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium Battery Smoke Alarm Model P4010ACS	
Bath Vents	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM	
Paddle Fan Boxes	Paddle fan rated boxes in all Bedrooms, Dining room, and Living room	
Cat 5 (data/phone)	Yes, per electrical plan	
TV Jacks	Yes, per electrical plan	
Security/Surveillance	None	
<u> </u>		
Central Vacuum	None	
Audio	None	
	Constitution of the Constitution of Atti-Const	
Solar Prep	Conduit running from LL up to Attic Space	
	Available as Option	



	Plumbing	
Heating and Venting		
Furnace	Ducane - 96G2UH045BV12	
Furnace Size	40,000 BTU	
Efficiency Rating	96%	4
Zones	Zone 1: First Floor	72
Second Zone	Available as Option	72
Air Conditioner	Available as Option	acces .
Thermostat	Ecobee Thermostat; First Floor	
Dath Martina	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
Bath Venting	Vented to the outside (Owners Bath and Bath #2)	
Dryer Venting	Vented to the outside	
Gas		
Main Kitchen Range	Yes	
Main Fireplace	Available as Option	
Dryer	No, Electric	
Furnace	Yes	
Hot Water System	Yes	
Grill Line at Deck	Available as Option	
Fireplace and Mantle		
Fireplace in Living Room	Available as Option	
Plumbing Fixtures		
	See Appendix D: Plumbing Schedule	
Miscellaneous Plumbing		
Outdoor Faucets	2 Frost-Free Hose Bibs, located at back of the main house and on the side of the front porch	
Hot Water Heater	State 50 Gallon Hybrid Electric water heater	
Laundry	Washer Box Valve with single handle shutoff and drain; appliances pricing optional	
	PVC Drainage plumbing.	
Plumbing	PEX continuous piping for all domestic water.	
	All plumbing installed according to National Plumbing Code by licensed plumber.	
Radon	Radon Piping runs from under Lower Level concrete slab through roof.	
Kauon	This is a passive system, no fan.	
Utility Sink	Available as Option	



	Cabinets & Countertops	
Cabinets		
Kitchen Upper Cabinets		
Brand	Fabuwood Galaxy/Allure/Luna	
Style	Full Overlay Doors	
Color	Color to be Frost	
Kitchen Island & Lower Perimeter		
Brand	Fabuwood Galaxy/Allure/Luna	
Style	Full Overlay Doors	
Color	Color to be Horizon	
Owner's Bath		
Size	72" Vanity with 2 bowls	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be Indigo	
Bath #2		
Size	42" Vanity with single bowl	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be Frost	
Countertops		
Kitchen		
Style	Classic Series Quartz	
Color	Helix	
Edge Detail	Pencil Edge	S. C. W. C. S. C.
Cut-Outs	Under Mount Sink	
Backsplash	4" Quartz	
B/S Location	Perimeter Back Only	
Kitchen Island		
Style	Classic Series Quartz	N A A A A A A A A A A A A A A A A A A A
Color	Helix	
Edge Detail	Pencil Edge	
Cut-Outs	None	
Owner's Bath		31
Style	Cultured Marble with 2 integrated flush rectangle bowls	
Color	Cotton White	M
Edge Detail	Square Edge	11
Cut-Outs Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
Bath #2		
Style	Cultured Marble with 1 integrated flush rectangle bowls	
Color	Cotton White	
Edge Detail	Square Edge	
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
In a lating	Wall & Trim Interior Detail Work	
Insulation	D. 24 Cll Ethanology Daths with Dalay Congress	
Exterior Walls	R-21 6" Fiberglass Batts with Poly Vapor Barrier	
Interior Walls	R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing)	
Rigid Insulation	Box sill in first and second floor joists insulated with rigid insulation	
Attic	R-60 Cellulose with backer boards at eves for ventilation	
Garage	Not insulated	
Foundation	2-1/2" R-15 Thermax glued to concrete wall	
Drywall	1/3ll Cheat Deal, toned with 2tfi-int	
Living area walls	1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings	
Ceilings	Smooth Finish, minor shadow variations are possible in ceilings	
Garage	Unfinished	
Trim Details	2.4/20/ Calanial Casina	
Casing	2-1/2" Colonial Casing	Table 1
Base	3-1/2" Colonial Base Board	
Wainscot	+/-60" High Wainscot at Mudroom under Black Metal Coat Hooks	
Crown	Available as Option	The state of the s



	I
Bench with Cubbies, Black Metal Coat Hooks	2
Plate Glass mirror with ground edge, no bevel	
<u></u>	
Carpet Grade Stairs	
Rail on wall stained	
Half wall, cap stained to match wood floor	
Satin Nickel	
All closets systems will be vented wire and the system is indicated on the plan.	
See Closet Plan for Details.	
1 coat primer	
2 coats Low VOC Flat Latex Paint, Color to be Classic Gray (OC-23)	Classic Gray
None	Classic Gray
To match walls	OC-23
Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
Color to be Snowfall White OC-118	
Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	Snowfall White
Color to be Snowfall White OC-118	OC-118
Painted, 2 coats of Semi-Gloss Latex Paint, Color to be Snowfall White OC-118	
Stained railing to Match Wood on First Floor	
See Door Appendix B: Exterior and Interior Door Schedule	
See Appendix E: Finish Hardware Schedule	
See Appendix F: Flooring Schedule	
See Appendix G: Appliance Schedule	
To be Selected by Owner, See Landscape Plan	
House cleaned prior to closing, including washing of windows	
Clearview Properties, LLC Warranty as per contract	
Continuing a policy of constant research and improvement, Clearview Properties, LLC reserves the right to make substitutions and specification changes.	
	Plate Glass mirror with ground edge, no bevel Plate Glass mirror with ground edge, no bevel Carpet Grade Stairs Rail on wall stained Half wall, cap stained to match wood floor Satin Nickel All closets systems will be vented wire and the system is indicated on the plan. See Closet Plan for Details. 1 coat primer 2 coats Low VOC Flat Latex Paint, Color to be Classic Gray (OC-23) None To match walls Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint, Color to be Snowfall White OC-118 Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint, Color to be Snowfall White OC-118 Painted, 2 coats of Semi-Gloss Latex Paint, Color to be Snowfall White OC-118 Stained railing to Match Wood on First Floor See Door Appendix B: Exterior and Interior Door Schedule See Appendix F: Flooring Schedule See Appendix F: Flooring Schedule All disturbed portions of yard to be seeded. Lawn area will generally include front yard, side yard and rear yard. Lawn area to be covered with approximately 4" of native topsoil. To be Selected by Owner, See Landscape Plan To be Selected by Owner, See Landscape Plan House cleaned prior to closing, including washing of windows Clearview Properties, LLC Warranty as per contract Continuing a policy of constant research and improvement, Clearview Properties, LLC reserves



SPRUCE HOME - CONSTRUCTION SPECIFICATIONS

Harvey Slimline All Vinyl Windows, Double insulated, Low E, GBG Grills 6 over 0 6 9/16 primed interior jambs, 2 1/2 colonial case interior J Channel Only (Brickmould) EZ-Tilt cleaning Screens included

Energy Star Qualified Maximum U Factor 0.30

Waximum o ractor c	Letter	Size	Quantity	Description	Location	lmage	Notes
	А	34x65	4	Double Hung	Dining Room, Living Room	Û	
	В	34x53	5	Double Hung	Owners Bedroom, Bedroom 3	Û	
	B2	68x53	2	Double Hung	Bedroom 2	Û Û	
	С	34x41	5	Double Hung	Powder Room, Bath 2, Upstairs Hall, Owners Bathroom	Û	
	D	34x49	1	Awning	Mudroom		
	E	42x49	1	Double Hung	Kitchen	Û	
	G	34x34	2	Awning	Living Room		
	G2	68x34	1	Awning	Dining		
	EG	55x48	1	Concrete Hopper	Lower Level		



SPRUCE HOME - CONSTRUCTION SPECIFICATIONS EXTERIOR DOORS

Therma-Tru Smooth Star Fiberglass Exterior Doors with full weather stripping and adjustable sills

Grills between glass

6 9/16 primed jambs

	Quantity	Description	Opens	Size	Туре	Hardware	Image	Notes
oyer Entry								
	1	S601-LE 1 Lite 2 panel with S210SL- LE Sidelite	LH	3'-0" - 6'8"	2 Panel	Double Bore		
Garage Entry								
	1	S220 2 Panel	RH	3'-0" - 6'8"	2 Panel	Double Bore		
Dining Room to De	ck							
	1	Harvey Vinyl Sliding Patio Door	RH	6'-0" - 8'-0"	Slider	Glass		RH active panel when viewed from Exterior
Exterior Door Hardv	vare							
Knobs	2	EZ - Set Keyed Entry w/deadbolt				Satin Nickel		All Keyed Alike
		·	IN ⁻	TERIOR DOORS				·
Colonial Casing both Dexter Stratus Satin Ball catches and (2)	sides	ardboard, 4 9/16 PFJ s	plit jambs					
nterior Doors					l I			I
	13	Masonite Smooth	See Plans - will display more clearly with plans	TBD	2 Panel Hollow Core	Double Bore		
nterior Door Hardw	are							
							Q _a	
Knobs	13	EZ - Set				Satin Nickel		

Base Bumps

Hinge Bumps

13

13

Satin Nickel

Satin Nickel



SPRUCE HOME - CONSTRUCTION SPECIFICATIONS							
	Quantity	Description	SKU	Item	Color	Image	Notes
Garage Exterior	1	One Light Outdoor Wall Lantern	143182	Maxim 35016BK	Black		
eck Exterior							
	1	One Light Outdoor Wall Lantern	143190	Maxim 35015BK	Black		
ront Porch							
	4	Click Lights - LED Flush Mount	040842	Green Creative	White		
oyer							
	1	LED Flush Mount	3535065	George Kovacs #P5550-44B-L	White		
Nain Hallway							
·	1	Click Lights - LED Flush Mount	040842	Green Creative	White		
Mudroom							
	2	Click Lights - LED Flush Mount	040842	Green Creative	White		
owder Room							
	1	Two Light Bath	97111	Elegant Lighting#: LD4033W21C	Chrome		
Citchen Island				1	I		
	2	One Light Mini Pendant	3310006	Meridian #M70118WHPN	White		
Kitchen				1			
	5	Click Lights - LED Flush Mount	040842	Green Creative	White		
(itchen Sink							
	1	Click Lights - LED Flush Mount	040842	Green Creative	White		



Nulley De aus									
Dining Room		1				I	I I		
	1	Five Light Chandelier	3242580	Visual Comfort Studio 3164205-05	Chrome				
Living Room									
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel	*			
Stairwell									
	6	Click Lights - LED Flush Mount	040842	Green Creative	White		To Second Floor and to Lower Level		
Upstairs Hallway									
,	2	Click Lights - LED Flush Mount	040842	Green Creative	White				
Owners Bedroom									
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel	*			
Owners Vanity									
	2	Two Light Bath	97111	Elegant Lighting#: LD4033W21C	Chrome				
Owners Closet									
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel				
Bedroom #2									
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel				
Bedroom #3									
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel				



Bath #2	Bath #2									
	1	Three Light Bath	97103	Elegant Lighting#: LD4033W33C	Chrome	* * *				
Other										
Garage, Future, Lower Level	9	PC Lights					Supplied by Electrician			



		SPRUCE HON	NE - CONSTRU	CTION SPECI	FICATIONS		TOMES
Kitchen	Qty.	Description	Manutacturer	Product No.	Finish	Image	Notes
Sink	1	32" Undermount 16 Gauge Stainless Steel Double Bowl Kitchen Sink	Krauss	KBU32	Stainless Steel		32" L x 18" W, 8.5"D, (2) Strainers and Grates
Faucet	1	Arbor Single-Handle Pull- Down Sprayer	Moen	7594C	Chrome		
Powder Room		<u>'</u>			·		
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6150	Chrome		
Pedestal Sink	1	Edgemere Pedestal Sink	American Standard	0445.400	White		
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Heigh
Owner's Bath							
Faucet	2	Eva Two-Handle Sink Faucet	Moen	6150	Chrome		
Shower	1	Medley Shower Stall - 60" x 34"	Sterling	72430100-0	White		Straight Curtain Ro Installed.
Shower Fixture	1	Eva Collection Eco- Performance Trim Kit	Moen	T2138EP	Chrome	9	Moen 2520 Showe Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Heigh



Bath #2	Bath #2								
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome				
Tub/Shower	1	60-1/4" x 32" Curce Bath/Shower with RH Drain	Sterling	71220110-0	White		Straight Curtain Rod Installed.		
Tub/Shower Trim	1	Eva Conversion Eco- Performance Tub/Shower Trim	Moen	T2139EP	Chrome		Moen 2520 Shower Valve		
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height		



							OMES
		SPRUCE HOM	E - CONSTRU	ICTION SPEC	IFICATIONS		
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes
Powder Room							
Tissue Holder	1	Arlys Paper Holder	Moen	Ү5708СН	Chrome		
Hand Towel Bar	1	Arlys Hand Towel Bar	Moen	Ү5786СН	Chrome		
Owner's Bath							
Knob	7	Blackrock - 1 5/16"	Amerock	BP5527026	Polished Chrome		
Robe Hook	1	Arlys Double Robe Hook	Moen	Y5703CH	Chrome		
Tissue Holder	1	Arlys Paper Holder	Moen	Y5708CH	Chrome		
Towel Bar	1	Arlys 24 in. Towel Bar	Moen	Y5724CH	Chrome	2	
Bath #2							
Knob	7	Blackrock - 1 5/16"	Amerock	BP5527026	Polished Chrome		
Robe Hook	1	Arlys Double Robe Hook	Moen	Ү5703СН	Chrome		
Tissue Holder	1	Arlys Paper Holder	Moen	Y5708CH	Chrome		
Towel Bar	1	Arlys 24 in. Towel Bar	Moen	Y5724CH	Chrome	R R	
(itchen Drawers & [Doors						
Pulls	24	BLACKROCK™ 3-3/4in(96mm) Center- To-Center Pull	Amerock	BP5527626	Chrome		



SPRUCE HOME - CONSTRUCTION SPECIFICATIONS

			\				
		A. .	Wood FI		1		ı
Location	Make	Style	Finish	Size		Image	
Foyer, Hallway, Kitchen, Dining Room	Lauzon Expert	Essential	Natural, Tradition - Hard maple	2 1/4"			3/4"
			Tile Flo	ors			
Location	Make/Style	Finish/Color	Tile Size	Orientation	Tile Grout	Image	Notes
Owner's Bath	Anatolia La Marca	Statuario Nuovo	12 x 24	Short Edge to the door	As recommended by EPC		Transitions to Dreamweaver Carpet
Mudroom and Powder Room	Antolia Nexus	Mica	12 x 24	Long Edge to the kitchen entry.	Dusty Grey		Standard Underlayment. Transitions to 7/16' Wood.
			Vinyl Flo	oors	*	•	*
	Make	Style	Color			Image	Notes
Bath #2	TruTex	Nero Hex	White	27131			Standard Underlayment. Transitions to Dreamweaver Carpet.



	Carpet								
	Make	Style	Color	Details	Image				
Living Room	Dreamweaver	Pinpoint	Stillwater	6014		Transitions to Dreamweaver Carpet			
Stairs to Second Floor and Second Floor Hallway	Dreamweaver	Pinpoint	Stillwater	6014		Transitions to Dreamweaver Carpet			
Owners Bedroom	Dreamweaver	Pinpoint	Stillwater	6014		Transitions to Tile			
Owners WIC	Dreamweaver	Pinpoint	Stillwater	6014		Transitions to Dreamweaver Carpet			
Bedroom #2 & #3	Dreamweaver	Pinpoint	Stillwater	6014		Transitions to Dreamweaver Carpet			



							ONES
		SPRUCE HO	OME - CONSTRU	CTION SPEC	IFICATIONS		
Appliance	Quantity	Manufacturer	Model	Color	Description	lmage	Notes
itchen							
Refrigerator	1	GE	GNE27JYMFS	Stainless	GE Energy Star 27.0 Cu. Ft. French Door		Fingerprint Resistant Door
Gas Range	1	GE	JGB735SPSS	Stainless	GE 30" Free Standing Convection Gas Range		
Dishwasher	1	GE	GDT550PYRFS	Stainless	GE Dishwasher with Top Controls	Hereb	
Microwave	1	GE	JVM3160RFSS	Stainless	GE 1.6 Cu. Ft. Over- the-Range- Microwave Oven		
aundry Room					_		
Washer							Available as optio
Electric Dryer							Available as optio