

#### **Model GL HOME - CONSTRUCTION SPECIFICATIONS**

Builder

Clearview Properties, LLC 1037 Hinesburg Road, Suite A South Burlington, VT 05403 Homeowner/Project Model Home Clearview #35 399 Horseshoe Circle

Milton VT, 05486

Specification Date: Site Plan Date: Plan Date: Electric Plan Date:

Model Plan: Two story home with partially finished lower level. Two floors of finished area with approximately 2,235 square feet of living space; 195 square feet of finished Lower Level, 462 square foot 2-car garage, and a 48 square foot front porch.

Location	Total Square Feet
First Floor	1,020
Second Floor	1,020
Lower Level	195
Total Finished Square Feet	2,235
Lower Level	341
Garage	462
Front Porch	48

**Personal Choice Lists** PCL# **Color Code** Date GRAPE **ORANGE GOLD GREEN** BLUE **PURPLE** PINK **HUNTER SKY BLUE LAVENDER BROWN** NAVY **CRANBERRY** AQUA PEACH RED

#### Specification and Appendix Approval

Appendix A: Window Schedule
Appendix B: Exterior and Interior Door Schedule
Appendix C: Lighting Schedule
Appendix D: Plumbing Schedule
Appendix E: Finish Hardware Schedule
Appendix F: Flooring Schedule
Appendix G: Appliance Schedule

Client		Date
Client		Date
Builder	Collin Frisbie	Date



Model GL HOME - CONSTRUCTION SPECIFICATIONS						
Section	Information	Image				
Permits						
	Builder responsible to obtain all necessary permits including:					
	- Soil Erosion and Sediment Control					
	- Zoning					
Surveys						
	Home is to be staked by builder					
ite Clearing	·					
<b>5</b>	Builder is responsible for all site clearing, as needed					
Jtilities Connections						
	Builder responsible for all site work and site balance to include					
Water	Connection to City of Milton water system					
Sewer	Connection to City of Milton sewer system					
Gas	Connection to Natural Gas lines at road.					
Power	Underground power					
Cable	Cable TV conduit to house					
	All excavation, fill and labor is included					
Energy Package	· · · · · · · · · · · · · · · · · · ·					
<i></i>	Home to be built to VT Residential Building Energy Standards (RBES)					
	Compliant with Act 250 Stretch Code					
Home to Include	, , , , , , , , , , , , , , , , , , ,					
	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.					
	Vented to the outside					
	Additional caulking and air sealing of joists to reduce air infiltration into the home, including shoe					
	plate; windows; and where wires and pipes go to cold spaces					
	R-15 Rigid Thermax insulation on Interior of Lower Level - floor to top of concrete wall					
	Selected use of closed cell foam to improve overall air sealing of attic in home					
	Blower Door Test as home completed required for VT RBES					
Solar Prep	Home solar ready with conduit running from LL up to Attic Space					
oundation	, , , , , , , , , , , , , , , , , , , ,					
Туре	Poured Concrete					
Wall Height	8'					
Lookout Height	4' Frost Wall					
Strength	Min. 3000 PSI @2 days with steel reinforcement					
Footer	Continuous 8" x 16" reinforced					
lat Work Concrete						
Lower Level	Poured Concrete					
Finish	Smooth					
"Keyway" Joints	Saw cut					
Thickness	4"					
Strength	House: Min. 3000 PSI @ 28 days Garage: Min. 4000 PSI @ 28 days					
	Tarred damp proofing membrane sprayed on exterior of foundation walls.					
Moisture Barrier	6 mil poly under concrete house slab.					
	Footing drains installed below footers around Lower Level and drained to daylight in back yard.					
Ground water controls	Drain tile buried in clean stone; covered with mirafi fabric; clean sand fill against foundation. Site					
	graded to shed surface water away from house.					
	Boulder rock walls as needed for the grading of the yard.					
Rock Wall	Boulders from the site are machine-placed to create walls.					
Slab Plumb	Not available with this home design					



		HOWES
Driveway/Entrance		
Drive	12" thick gravel two car driveway on top of mirafi fabric.	
Drive	Driveway to be finish paved with 2" of compacted asphalt.	
Walkway	42" Sidewalk from front porch to driveway	
Frame		
Exterior Walls	2x6 SPF 24" o.c.	
Interior Walls	2x4 SPF 24" o.c.	
Plate Height	9'-1" on first floor; 8'-1" on second floor and 8' in lower level	
Plate	2x6 treated southern yellow pine with foam sill seal	
Floor Framing	2x10 SPF 19.2" o.c.	
Sub Flooring	3/4" 4x8 T&G OSB glued and nailed	
	2 or 3 ply 2x12, nailed and glued, as specified by engineering load design, supported by 3-1/2"	
Girders	concrete filled lally columns in Lower Level	
Sheathing	7/16" 4x8 OSB	
Roof	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting	
Roof Pitch	Pitches: 8/12 and 10/12 at Main House; 10/12 at Front Porch	
House Wrap	Professional house wrap with flashing around all windows and doors	
Roofing	1. Totessional mouse wrap with hashing around all willdows and doors	
nooning .	Ice and water shield on eaves and valleys. Vented on ridge to achieve proper ventilation.	
Underlayment	Owens Corning ProArmor Synthetic Roof Underlayment	
Shingles	Owens Corning ProAfficial Synthetic Roof Orderlayment  Owens Corning TruDefinition Shingles Limited Lifetime Warranty	
Color		
	Color to be Selected by Owner	
Siding/Exterior Elements	Navanday Waadaman Calaat	
Siding Cable Ends	Norandex Woodsman Select Shakes, Color to selected by owner	
Gable Ends		
Clapboard	Double 4", Color to be selected by owner	
Board and Baton	None White	
Eaves	Two piece aluminum wrapped - White	
Soffit	Perforated soffit for proper venting	
Corners	6" White Vinyl Corners with Foam Backer	
Trim Details	Frieze board and Garage Door Trim to be PVC	
Drip Edge	Galvanized	
Shutters  Cuttors & Downson outs	Available as Option	
Gutters & Downspouts	White Country Cottons	
Gutters & Downspouts Windows	White Seamless Gutters	
windows	Coo Annandiy A. Window Schodula	
Drond	See Appendix A: Window Schedule	
Brand	Harvey Slimline	
Color	White	
Construction  Exterior Casing	Vinyl, Low-E, Insulated Double-Pane	
Exterior Casing	J Channel Only (Brickmould)	
U-Factor	0.30	
Grills	Grills Between Glass 6 over 0	
Screens  Exterior Doors	Fiberglass Mesh	
Exterior Doors	Con Annondiy D. Eytovicy and Interior Dear Cahadula	
P d	See Appendix B: Exterior and Interior Door Schedule	
Brand	Therma-Tru	
Color	See Exterior Paint Section	
Construction	Insulated Fiberglass	
Exterior Casing	5/4x4 Flat	
Storm Doors	None	



Overhead Garage Doors		
Model	8300 Series Insulated Steel Door	
Size	16' x 7'	
Design	Colonial Raised Panel Door	
Color	Manufacturer White	
Opener	8" lift master 1/2 horsepower electric opener	
Remotes	2 remotes included	
Frame Key Pad	Keyless entry punch pad	
Decks & Porches		
Covered Entry Porch		
Porch Framing	6' x 8' Patio Pavers, No Joists or Decking	
Decking	5/4x6 PT decking	
Posts	PVC wrapped and PT 6x6 Posts, 2x8 roof beams - White. Posts wrapped top and bottom.	
Roof	Roof to be truss framed, roof shingles to match house	
Ceiling	White vinyl bead board	
Stairs	No Steps	
Rail	Available as an Option	
Finish	Porch posts, beams	
Color	Porch decking and stair tread stained with Total Wood Preservative - Selected by Owner	
Deck	14' x 12' Deck Available as Option	
Exterior Paint		
Exterior Doors - Excluding Front Door	Painted Satin Finish, White	
Exterior Trim - Including Frieze Board and Door Surrounds	Painted Satin Finish, White	
Front Door	2 coats Exterior Paint, Color to be Selected by Owner	
Sidelight	Painted Satin Finish, White	
Front Porch Rail	Pressure Treated - painted white	
Front Porch Posts	Painted White	
Front Porch Roof Beams	Painted White	



trical & Low Voltage		
	Underground electrical service, 40 circuit 150 AMP Panel with Surge Protection. Open double slot for future solar.	
Plugs and Switches		
Switch Style	Toggle	4
Plate Style	Toggle screw on plates	
Switch Color	White	
Dimmers	Available as Option	
Exterior Plugs	Per Electrical Plan	0
Lighting	Tel Electrical Full	
Lighting Fixtures	See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	
Recessed Lights	None	
Under Cabinet Lighting	Available as Option	
Miscellaneous	Available as Option	
	GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished	
Outlets	areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.	
Door Chime	Nutone BK125LWH: One 2-note, white door chime	
Smoke/CO	1 CO/Smoke per floor (3 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium Battery Smoke Alarm Model P4010ACS	
Bath Vents	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM	
Paddle Fan Boxes	Paddle fan rated boxes in all Bedrooms, Dining room, and Living room	
Cat 5 (data/phone)	Yes, per electrical plan	
Coax Cable	Yes, per electrical plan	
Security/Surveillance	None	
Central Vacuum	None	
Audio	None	
Solar Prep	Conduit running from LL up to Attic Space	
Garbage Disposal	Available as Option	
tht Fixtures	Available as Option	
int rixtures	See Appendix C: Light Fixture Schedule	
	Plumbing	
eating and Venting		
Furnace	Ducane	
Furnace Size	45,000 BTU	
Efficiency Rating	96%	
Zones	Zone 1: First Floor, Second Floor, Lower Level	72
Second Zone	Available as an Option	72
Air Conditioner	Available as an Option	***
Thermostat	Ecobee Thermostat; First Floor and Second Floor	
Bath Venting	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.  Vented to the outside	
Dryer Venting	Microwave/Hood Vent vented to the outside	
as	maioriary noon rene renied to the outside	
Main Kitchen Range	Yes	
Main Fireplace	Available as Option	
Floor Dryer	No	
Furnace	Yes	
Hot Water System	Yes	
Grill Line at Deck		
	Available as Option	
replace and Mantle		
Fireplace and Mantle Fireplace in Living Room umbing Fixtures		



		HOWES
Miscellaneous Plumbing		
Outdoor Faucets	2 Frost-Free Hose Bibs, located at back of the main house and on the side of the front porch	
Hot Water Heater	State 50 Gallon Hybrid Electric water heater	
Laundry	Washer Box Valve with single handle shutoff and drain; appliances pricing optional	
	PVC Drainage plumbing.	
Plumbing	PEX continuous piping for all domestic water.	
	All plumbing installed according to National Plumbing Code by licensed plumber.	
Radon	Radon Piping runs from under Lower Level concrete slab through roof.	
Kadon	This is a passive system, no fan.	
Utility Sink	Available as an Option	
	Cabinets & Countertops	
Cabinets		
Kitchen		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Kitchen Island		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Owner's Bath		
Size	72" Vanity with 2 bowls	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Bath #2		
Size	60" Vanity with single bowl	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Countertops		
Kitchen		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	C C
Cut-Outs	Under Mount Sink	
Backsplash	4" Classic Series Quartz	
B/S Location	Perimeter Back Only	
Kitchen Island	Termeter back only	
Style	Classic Series Quartz	
	To Be Selected by Owner	
Edge Detail	Pencil Edge	
Cut-Outs	None	Kitchen Tops (not color or Style)
Owner's Bath	HOIC	
	Cultured Marble with 2 integrated flush rectangle bowls	315
Style Color	Cotton White	111
Edge Detail	Square Edge	NE
Cut-Outs	· · ·	
	None  4" integral Cultured Marble	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
Bath #2	Cultivard Markla with 1 integrated floor action at head	
Style	Cultured Marble with 1 integrated flush rectangle bowls	
Color	Cotton White	WA.
Edge Detail	Square Edge	
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	



		HOMES
	Wall & Trim Interior Detail Work	
Insulation		
Exterior Walls	R-21 6" Fiberglass Batts with Poly Vapor Barrier	
Interior Walls	R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing)	
Rigid Insulation	Box sill in first and second floor joists insulated with rigid insulation	
Attic	R-60 Cellulose with backer boards at eves for ventilation	1
Garage	Not insulated	1
Foundation	2-1/2" R-15 Thermax glued to concrete wall	1
Drywall	, ,	•
Living area walls	1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings	
Ceilings	Smooth Finish, minor shadow variations are possible in ceilings	1
Garage	5/8" at Celling Only, 1 Coat Tape and Mud	1
Trim Details	Joyo at sening only) I seat tape and mad	1
Casing	2-1/2" Colonial Casing	
Base	3-1/2" Colonial Base Board	-
Crown	Available as Option	1
Built - Ins	[Αναιιανίο αν Ορτίοι]	
Mirrors		
Owners Bath	Plate Glass mirror with ground edge, no bevel	
Bath #2	Plate Glass mirror with ground edge, no bevel	
Powder Room	By Owner	
	by Owner	200
Interior Stairs/Railing	County County Chairm	
Main to Second Floor	Carpet Grade Stairs	
	First Floor to Landing to be half wall with a hardwood cap and railing on wall. Cap to be Maple,	
	sealed Natural.	
	Rail on wall stained	
Main to Lower Level	Carpet Grade Stairs	
	Rail on wall stained	
Handrail Brackets	Satin Nickel	
Closet Shelving		
	All closets systems will be vented wire and the system is indicated on the plan.	
	See Closet Plan for Details.	
Interior Paint		
Painted Interior Walls	1 coat primer	
- antea menor trans	2 coats Low VOC Flat Latex Paint, Color to be selected by owner.	
Accent Wall	None	
Ceilings	To match walls	
Interior Trim	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
interior ITilli	Color to be Selected by Owner, OK to Color Match	
Mainsont	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
Wainscot	Color to be Selected by Owner, OK to Color Match	
lintarian Dania	Deleted 2 and of Comi Charleton Delete Coloredo ha Col	
Interior Doors	Painted, 2 coats of Semi-Gloss Latex Paint, Color to be Selected by Owner, OK to Color Match	
Fireplace Mantle (optional)		
, , ,		<del> </del>
	Rail and Newel Sealed and Matching Wood Floor	
Main to Second Floor Stairs	Rail and Newel Sealed and Matching Wood Floor Baluster Posts Painted to Match Interior Trim	



		11 0 111 2 0
Interior Doors		
	See Door Appendix B: Exterior and Interior Door Schedule	
Finish Hardware		
	See Appendix E: Finish Hardware Schedule	
Flooring		
	See Appendix F: Flooring Schedule	
Appliances		
	See Appendix G: Appliance Schedule	
Landscaping		
	All disturbed portions of yard to be seeded.	
Lawn	Lawn area will generally include front yard, side yard and rear yard.	
	Lawn area to be covered with approximately 4" of native topsoil.	
8 Foundation Shrubs	To be Selected by Owner, See Landscape Plan	
8 Perennial Flowers	To be Selected by Owner, See Landscape Plan	
Cleaning		
	House cleaned prior to closing, including washing of windows	
Warranty		
	Clearview Properties, LLC Warranty as per contract	
	Continuing a policy of constant research and improvement, Clearview Properties, LLC reserves	
	the right to make substitutions and specification changes.	
	<u> </u>	



#### **Appendix A: Window Schedule**

Harvey Slimline All Vinyl Windows, Double insulated, Low E, GBG Grills 6 over 0 6 9/16 primed interior jambs, 2 1/2 colonial case interior J Channel Only (Brickmould) EZ-Tilt cleaning Screens included

Energy Star Qualified Maximum U Factor 0.30

Letter	Size	Quantity	Description	Location	lmage	Notes
А	34x65	6	Double Hung	Living Room, Den, Office, Stairwell		
A2	68x65	1	Double Hung	Dining Room		
В	34x53	5	Double Hung	Den, Owner's Bedroom, Bedroom #3		
B2	68x53	1	Double Hung	Bedroom # 2	ÛÛ	
С	34x41	4	Double Hung	Powder Room, Laundry, Bath #2, Office	Û	
D	36x14	1	Fixed	Owner Bath		
н	34x49	1	Double Hung	Owners Bath	Û	
К	42x49	1	Double Hung	Kitchen		



### Appendix B: Exterior and Interior Door Schedule EXTERIOR DOORS

Therma-Tru Smooth Star Fiberglass Exterior Doors with full weather stripping and adjustable sills

6 9/16 primed jambs

5/4 x 4 flat exterior case, Double bore set-up

EZ Set Satin Nickel knob and deadbolt hardware, All doors keyed alike

	Quantity	Description	Opens	Size	Type	Hardware	Image	Notes
Foyer Entry								
	1	S601 with S210SL Sidelite	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Garage Entry								
	1	S220 2 Panel	LH	3'-0" 6'-8"	2 Panel	Double Bore		
Garage To Storage		·						
	2	\$220 2 Panel	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Foyer To Storage								
	1	S220 2 Panel	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Living to Future Dec	k							
	1	7280 Harvey Sliding Patio Door	LH	6'-0" 6'-8"	Slider	Glass		Left Panel Active when viewed from exterior
Exterior Door Hardw	are							
Knobs	4	EZ - Set Keyed Entry w/deadbolt				Satin Nickel	<b>F</b>	All Keyed Alike



	INTERIOR DOORS							
2 Panel, Hollow core Colonial Casing both EZ-Set Satin Nickel H Ball catches and (2) [	sides ardware							
Interior Doors								
	15	Masonite Smooth	See Plans - will display more clearly with plans	TBD	2 Panel Hollow Core	Double Bore		
	4	Masonite Smooth	See Plans - will display more clearly with plans	TBD	Double Doors	Double Bore		Foyer, Office, BR #2, BR #3
Interior Door Hardw	are							
Knobs	15	EZ - Set				Satin Nickel		
Knobs	8	EZ - Set				Satin Nickel		Dummy for Ball Latch Double Doors
Base Bumps	25					Satin Nickel		
Hinge Bumps	25					Satin Nickel	3	



Appendix C: Light Fixture Schedule										
	Quantity	Description	SKU	Item	Color	Image	Notes			
Garage Exterior										
	1	One Light Outdoor Wall Lantern	534299	Maxim 1024PE	Pewter					
Deck Exterior										
	1	One Light Outdoor Wall Lantern	967425	Maxim 1025PE	Pewter					
ront Porch										
	2	Click Lights - LED Flush Mount	040842	Green Creative	White					
Foyer										
	1	Three Light Semi Flush Mount	738584	Kichler 43669NI	Brushed Nickel					
	2	Click Lights - LED Flush Mount	040842	Green Creative	White					
Office										
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	*				
Kitchen Island										
	2	One Light Mini Pendant	738588	Kichler 43668NI	Brushed Nickel					
Kitchen										
	6	Click Lights - LED Flush Mount	040842	Green Creative	White					



Dining Day							I O IVI E S
Dining Room				I			
	1	Five Light Chandelier	738590	Kichler 43665NI	Brushed Nickel	27.00	
Living Room				I		I	I
	2	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel		
Powder							
	1	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		Pointed Down
Laundry Room							
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	*	
Powder Room/Laun	dry Hall						
	1	Click Lights - LED Flush Mount	040842	Green Creative	White		
Den							
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel		
Stairwells				I		I	
	3	One Light Wall Sconce	738960	Kichler 45568NI	Brushed Nickel	(j)	1 - Main to Second Floor and 1 - in Main to Lower Level
Upstairs Hall							
	3	Click Lights - LED Flush Mount	040842	Green Creative	White		
Owners Bedroom							
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel		



							OMES
Owners Vanity						I	
	2	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		Pointed Down
Owners W/C							
	1	Click Lights - LED Flush Mount	040842	Green Creative	White		
Owners Closet - eac	ch	·					
	2	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel		
Bedroom #2						1	
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel		
Bedroom #3							
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel		
Bath #2						I	
	1	Three Light Bath	738938	Kichler 45570NI	Brushed Nickel		Pointed Down
Other							
Garage, Mech Space	TDB	PC Lights					Supplied by Electrician
		1					



						ŀ	HOMES
		App	endix D: Plun	nbing Sched	ule		
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes
Kitchen	•						
Sink	1	32" Undermount 16 Gauge Stainless Steel Double Bowl Kitchen Sink	Krauss	KBU32	Stainless Steel		32" L x 18" W, 8.5"D (2) Strainers and Grates
Faucet	1	Arbor Single-Handle Pull- Down Sprayer	Moen	7594C	Chrome		
Owner's Bath							-
Faucet	2	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	70	
Shower Stall	1	Ensemble Curve 60" Shower Stall	Sterling	72230100-0	White	1000	
Shower Fixture	1	Eva Collection Eco- Performance Trim Kit	Moen	T2132	Chrome	6	Moen 2520 Shower Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height



Bath #2							HOMES
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	70	
Tub/Shower Trim	1	Ensemble 60" x 32" Tub/Shower with LH drain	Sterling	71220110-0	White		Straight Curtain Rod Installed.
Tub/Shower Trim	1	Eva Conversion Eco- Performance Tub/Shower Trim	Moen	T2133	Chrome		Moen 2520 Shower Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height
Powder Bath							
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	7	
Pedestal Sink	1	Edgemere Pedestal Sink	American Standard	0445.400	White	T	
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height



Appendix E: Finish Hardware Schedule									
Owner's Bath	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes		
Jwilet's Balli									
Knob	7	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel	9			
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome				
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome				
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome	3			
owder Bath									
Towel Ring	1	Eva Bathroom Hand Towel Ring	Moen	YB2886CH	Chrome	5			
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome				
Bath #2					<u>'</u>	· · · · · · · · · · · · · · · · · · ·			
Knob	7	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel	-			
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome				
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome				
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome				
Citchen Surround									
Knob	18	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel				
itchen Island									
Knob	4	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel	8			
					1				



#### **Appendix F: Flooring Schedule**

			WOO	D			
Location	Make	Style	Finish	Size		Image	
1st Floor Hallway Kitchen Dining Room Living Room	Lauzon	Expert	TBD	TBD			Height 3/4"
			TILE				·
ocation	Make/Style	Finish/Color	Tile Size	Orientation	Tile Grout	Image	Notes
Owner's Bath	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to Mudroom Tile.
Powder Room	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to Mudroom Tile.
					·		
Foyer	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to Mudroom Tile.



Make	61.1	CARF				
	Style	Color	Details		Image	
						<u>'</u>
Dreamweaver	Pinpoint	TBD				Transitions to 3/4" Wood.
					I	
Dreamweaver	Pinpoint	TBD				Transitions to Owners Bath Tile.
Dreamweaver	Pinpoint	TBD				Transitions to Dreamweaver Carpet.
						·
Dreamweaver	Pinpoint	TBD				Transitions to 3/4" Wood.
					_	
Dreamweaver	Pinpoint	TBD				Transitions to Tile
				ı		
Make	Style	Color	Details		Image	
					I I	
Tarkett	Fresh Start	TBD	TBD	TBD		Transitions to Carpet
Tarkett	Fresh Start	TBD	TBD	TBD		Transitions to Woo
	Dreamweaver  Dreamweaver  Dreamweaver  Make  Tarkett	Dreamweaver Pinpoint  Dreamweaver Pinpoint  Dreamweaver Pinpoint  Make Style  Tarkett Fresh Start	Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  VINY Make Style Color  Tarkett Fresh Start TBD	Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  VINYL  Make Style Color Details  Tarkett Fresh Start TBD TBD	Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  VINYL  Make Style Color Details  Tarkett Fresh Start TBD TBD TBD	Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  Dreamweaver Pinpoint TBD  VINYL  Make Style Color Details Image  Tarkett Fresh Start TBD TBD TBD



						F	IOMES
		Ap	pendix G: Appl	liance Sche	dule		
Appliance	Quantity	Manufacturer	Model	Color	Description	Image	Notes
itchen							
Refrigerator	1	GE	GNE27JYMFS	Stainless	GE Energy Star 27.0 Cu. Ft. French Door	1	Fingerprint Resistant Door
Gas Range	1	GE	JGB735SPSS	Stainless	GE 30" Free Standing Gas Convection Range		
Dishwasher	1	GE	GDT550PYRFS	Stainless	GE Dishwasher with Top Controls	•	
Microwave	1	GE	JVM3160RFSS	Stainless	GE 1.6 Cu. Ft. Over- the-Range- Microwave Oven		
aundry Room							
Washer							Available as optio
Electric Dryer							Available as optic