

#### **HOME - CONSTRUCTION SPECIFICATIONS**

#### Builder Homeowner/Project Specification Date: 8/31/23 Sterling Homes Properties LLC Site Plan Date: 1037 Hinesburg Road, Suite A Maddies Way # Plan Date: 8/21/23 South Burlington, VT 05403 Electric Plan: 8/21/23 Allen Plan: Two story home with unfinished lower level. Two floors of finished area with approximately 1,568 square feet of living space; 784 square feet of unfinished Lower Level, 484 square foot 2car garage, and a 60 square foot front porch. Location **Total Square Feet** First Floor 784 Second Floor 784

**Total Finished Square Feet** 

Lower Level

Garage

**1,568** 784

484

Galage	404			
Front Porch	60			
		Personal Choice Lists		
PCL #		Color Code		Date
		GRAPE		
		ORANGE		
		GREEN		
		BLUE		
		PURPLE		
		PINK		
		HUNTER		
		SKY BLUE		
		LAVENDER		
		BROWN		
		NAVY		
		CRANBERRY		
		AQUA		
		PEACH		
		RED		
		Specification and Appendix Approval		
		Appendix A: Window Schedule		
		Appendix B: Exterior and Interior Door Schedule		
		Appendix C: Lighting Schedule		
		Appendix D: Plumbing Schedule		
		Appendix E: Finish Hardware Schedule		
		Appendix F: Flooring Schedule		
		Appendix G: Appliance Schedule		
Client			Date	
Client			Date	
Builder	Collin Frisbie		Date	

1 of 19



	HOME - CONSTRUCTION SPECIFICATIONS					
Section	Information	Image				
Permits						
	Builder responsible to obtain all necessary permits including:					
	- Soil Erosion and Sediment Control					
	- Zoning					
Surveys		1				
	Home is to be staked by builder					
Site Clearing						
	Builder is responsible for all site clearing, as needed					
Utilities Connections		1				
	Builder responsible for all site work and site balance to include					
Water	Connection to Town of Colchester water system					
Sewer	Connection to Community Septic with Leach Field					
Gas	Connection to Natural Gas lines at road.					
Power	Underground power					
Cable	Cable TV conduit to house					
	All excavation, fill and labor is included					
Energy Package		1				
	Home to be built to VT Residential Building Energy Standards (RBES)					
	Compliant with Act 250 Stretch Code					
Home to Include						
	Panasonic WhisperLite <sup>™</sup> Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light. Vented to					
	the outside					
	Additional caulking and air sealing of joists to reduce air infiltration into the home, including shoe plate;					
	windows; and where wires and pipes go to cold spaces					
	R-15 Rigid Thermax insulation on Interior of Lower Level - floor to top of concrete wall					
	Selected use of closed cell foam to improve overall air sealing of attic in home					
	Blower Door Test as home completed required for VT RBES					
Solar Prep	Home solar ready with conduit running from LL up to Attic Space					
Foundation		1				
Туре	Poured Concrete					
Wall Height	7'10"					
Lookout Height	4' Frost Wall					
Strength	Min. 3000 PSI @2 days with steel reinforcement					
Footer	Continuous 8" x 16" reinforced					
Flat Work Concrete		1				
Lower Level	Poured Concrete					
Finish	Smooth					
"Keyway" Joints	Saw cut					
Thickness	4"					
Strength	House: Min. 3000 PSI @ 28 days Garage: Min. 4000 PSI @ 28 days					
Moisture Barrier	Tarred damp proofing membrane sprayed on exterior of foundation walls.					
	6 mil poly under concrete house slab.					
	Footing drains installed below footers around Lower Level and drained to daylight in back yard. Drain tile					
Ground water controls	buried in clean stone; covered with mirafi fabric; clean sand fill against foundation. Site graded to shed					
	surface water away from house.					
Rock Wall	Boulder rock walls as needed for the grading of the yard.					
	Boulders from the site are machine-placed to create walls.					
Lower Level Slab Plumb	Available as an Option					



Driveway/Entrance		
	12" thick gravel two car driveway on top of mirafi fabric.	
Drive	Driveway to be finish paved with 2" of compacted asphalt.	
Walkway	42" Sidewalk from front porch to driveway	
Frame		
Exterior Walls	2x6 SPF 24" o.c.	
Interior Walls	2x4 SPF 24" o.c.	
Plate Height	9'-1" on first floor; 8'-1" on second floor and 7'10" in lower level	
Plate	2x6 treated southern yellow pine with foam sill seal	
Floor Framing	2x10 SPF 19.2" o.c.	
Sub Flooring	3/4" 4x8 T&G OSB glued and nailed	
	2 or 3 ply 2x12, nailed and glued, as specified by engineering load design, supported by 3-1/2" concrete	
Girders	filled lally columns in Lower Level	
Sheathing	7/16" 4x8 OSB	
Roof	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting	
Roof Pitch	Pitches: 7/12 at Main House; 12/12 at Garage; 6/12 at Front Porch	
House Wrap	Professional house wrap with flashing around all windows and doors	
Roofing		
	Ice and water shield on eaves and valleys. Vented on ridge to achieve proper ventilation.	
Underlayment	Owens Corning ProArmor Synthetic Roof Underlayment	
Shingles	Owens Corning TruDefinition Shingles Limited Lifetime Warranty	
Color	To be selected by Owner	
Siding/Exterior Elements		
Siding	Norandex Woodsman Select	
Gable Ends	Double 4" Color to selected by owner	
Clapboard	Double 4", Color to be selected by owner	
Board and Baton	None	
Eaves	Two piece aluminum wrapped - White	
Soffit	Perforated soffit for proper venting	
Corners	6" White Vinyl Corners with Foam Backer	
Trim Details	Frieze board and Garage Door Trim to be PVC	
Drip Edge	Galvanized	
Shutters	Available as Option	
Gutters & Downspouts		
Gutters & Downspouts	White Seamless Gutters	
Windows		
	See Appendix A: Window Schedule	
Brand	Harvey Slimline	
Color	White	
Construction	Vinyl, Low-E, Insulated Double-Pane	
Exterior Casing	J Channel Only (Brickmould)	
U-Factor	0.30	
Grills	Grills Between Glass 6 over 0	
Screens	Fiberglass Mesh	
Exterior Doors		
	See Appendix B: Exterior and Interior Door Schedule	
Brand	Therma-Tru	
Color	See Exterior Paint Section	
Construction	Insulated Fiberglass	
Exterior Casing	5/4x4 Flat	
Storm Doors	None	



8300 Series Insulated Steel Door	
6' x 10' framed with PT 2x8 joists	
· ·	
14 x 12 Deck Available as Option	
Dainted Satia Einich White	
Painteu Saun Finish, White	
Painted Satin Finish, White	
· · ·	
Stained. Color to be Selected by Owner.	
Stained. Color to be Selected by Owner.	
Toggle	
	T
	T.
Toggle screw on plates	a IT
Toggle screw on plates White	a [F]
Toggle screw on plates         White         Available as Option	
Toggle screw on plates White	a      a
Toggle screw on plates         White         Available as Option         Per Electrical Plan	a  E  a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	a [1] a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None	a [] a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	a E a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option	a [7] a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None	
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option	a [F] a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of	a [] u
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.	
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime	0 0
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium	0 0
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS	
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM	0 0
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM         Paddle fan rated boxes in all Bedrooms, Dining room, and Living room	a a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM         Paddle fan rated boxes in all Bedrooms, Dining room, and Living room         Yes, per electrical plan	a a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM         Paddle fan rated boxes in all Bedrooms, Dining room, and Living room         Yes, per electrical plan         Yes, per electrical plan	0 0
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM         Paddle fan rated boxes in all Bedrooms, Dining room, and Living room         Yes, per electrical plan         Yone         None	a a
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM         Paddle fan rated boxes in all Bedrooms, Dining room, and Living room         Yes, per electrical plan         Yes, per electrical plan         None         None	0 0
Toggle screw on plates         White         Available as Option         Per Electrical Plan         See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)         None         Available as Option         GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.         Nutone BK125LWH: One 2-note, white door chime         1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year Lithium         Battery Smoke Alarm Model P4010ACS         Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM         Paddle fan rated boxes in all Bedrooms, Dining room, and Living room         Yes, per electrical plan         Yone         None	0 0
	16' x 7'         Colonial Raised Panel Door         Manufacturer White         8" lift master 1/2 horsepower electric opener         2 remotes included         Keyless entry punch pad         6' x 10' framed with PT 2x8 joists         5/4x6 PT decking         PVC wrapped and PT 6x6 Posts, 2x8 roof beams - White. Posts wrapped top and bottom.         Roof to be truss framed, roof shingles to match house         White vinyl bead board         Stairs from porch to walkway to be PT box steps with 5/4x6 PT treads.         Available as an Option         Porch posts, beams - White CPVC Trim         Porch posts, beams - White CPVC Trim         Porch decking, stair tread, risers and PT Rim stained with Total Wood Preservative - Selected by Owner         14' x 12' Deck Available as Option         Painted Satin Finish, White         2 coats Exterior Paint, Color to be Selected by Owner         2 coats Exterior Paint, Color to be Selected by Owner         Available as an Option         CPVC Wrapped, White         CPVC Wrapped, White         Stained. Color to be Selected by Owner.         St



Light Fixtures		
	See Appendix C: Light Fixture Schedule	
	Plumbing	
Heating and Venting		
Furnace	Ducane - 96G2UH045BV12	
Furnace Size	40,000 BTU	
Efficiency Rating	96%	1
Zones	Zone 1: First Floor and Second Floor	72
Second Zone	Available as Option	
Air Conditioner	Available as Option	
Thermostat	Ecobee 3 Thermostat; First Floor	34
Delle Marshine	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light. Vented to	
Bath Venting	the outside	
Dryer Venting	Microwave/Hood Vent vented to the outside	
Gas		
Main Kitchen Range	Yes	
Main Fireplace	Available as Option	
Dryer	No, Electric	
Furnace	Yes	
Hot Water System	Hybdid Electric	
Grill Line at Deck	Available as Option	
Fireplace and Mantle		
Fireplace in Living Room	Available as Option	
Plumbing Fixtures		
	See Appendix D: Plumbing Schedule	
Miscellaneous Plumbing		
Outdoor Faucets	2 Frost-Free Hose Bibs, located at back of the main house and on the side of the front porch	
Hot Water Heater	State 50 Gallon Hybrid Electric water heater	
Laundry	Washer Box Valve with single handle shutoff and drain; appliances pricing optional	
	PVC Drainage plumbing.	
Plumbing	PEX continuous piping for all domestic water.	
	All plumbing installed according to National Plumbing Code by licensed plumber.	
Radon	Radon Piping runs from under Lower Level concrete slab through roof.	
	This is a passive system, no fan.	
Utility Sink	Available as Option	



	Cabinets & Countertops	
Cabinets		
Kitchen		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Kitchen Island		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Owner's Bath		
Size	72" Vanity with 2 bowls	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Bath #2		
Size	42" Vanity with single bowl	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Countertops		
Kitchen		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	
Cut-Outs	Under Mount Sink	
Backsplash	4" Classic Series Quartz	
B/S Location	Perimeter Back Only	
Kitchen Island		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	
Cut-Outs	None	Kitchen Tops (not color or Style)
Owner's Bath		
Style	Cultured Marble with 2 integrated flush rectangle bowls	J. C.
Color	Cotton White	Me
Edge Detail	Square Edge	120
Cut-Outs	None	1
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
Bath #2		
Style	Cultured Marble with 1 integrated flush rectangle bowls	
Color	Cotton White	
Edge Detail	Square Edge	
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	



Wall & Trim Interior Detail Work

	Wall & Trim Interior Detail Work	
Insulation		
Exterior Walls	R-21 6" Fiberglass Batts with Poly Vapor Barrier	
Interior Walls	R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing)	
Rigid Insulation	Box sill in first and second floor joists insulated with rigid insulation	
Attic	R-60 Cellulose with backer boards at eves for ventilation	
Garage	Not insulated	
Foundation	2-1/2" R-15 Thermax glued to concrete wall	
Drywall		
Living area walls	1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings	
Ceilings	Smooth Finish, minor shadow variations are possible in ceilings	
Garage	Unfinished	
Trim Details		
Casing	2-1/2" Colonial Casing	
Base	3-1/2" Colonial Base Board	
Wainscot	+/-60" High Wainscot at Mudroom under Black Metal Coat Hooks, 40" High in Powder Room	
Crown	Available as Option	
Built - Ins		
	Black Metal Hooks at Mudroom	2
Mirrors		
Owners Bath	Plate Glass mirror with ground edge, no bevel	
Bath #2	Plate Glass mirror with ground edge, no bevel	
Powder Room	By Owner	
Interior Stairs/Railing		
Main to Second Floor	Carpet Grade Stairs	
	First Floor to Landing to be half wall with a hardwood cap and railing on wall. Cap to be Maple, sealed	
	Natural.	
	Rail on wall stained	
Main to Lower Level	Carpet Grade Stairs	
	Rail on wall stained	and the second s
Handrail Brackets	Satin Nickel	
Closet Shelving		
	All closets systems will be vented wire and the system is indicated on the plan.	
	See Closet Plan for Details.	
Interior Paint		1
Painted Interior Walls	1 coat primer	
	2 coats Low VOC Flat Latex Paint, Color to be selected by owner, OK to Color Match	_
Accent Wall	None	_
Ceilings	To match walls	_
Interior Trim	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
	Color to be selected by owner, OK to Color Match	_
Wainscot	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
	Color to be selected by owner, OK to Color Match	_
Interior Doors	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
	Color to be selected by owner, OK to Color Match	_
Main to Second Floor Stairs	Rail and Newel Sealed and Matching Wood Floor	
	Baluster Posts Painted to Match Interior Trim	
Main to Lower Level Stairs	Stained railing to Match Wood on First Floor	
Fireplace Mantle (optional)		



Interior Doors		
	See Door Appendix B: Exterior and Interior Door Schedule	
Finish Hardware		
	See Appendix E: Finish Hardware Schedule	
Flooring		
	See Appendix F: Flooring Schedule	
Appliances		
	See Appendix G: Appliance Schedule	
Landscaping		
	All disturbed portions of yard to be seeded.	
Lawn	Lawn area will generally include front yard, side yard and rear yard.	
	Lawn area to be covered with approximately 4" of native topsoil.	
8 Foundation Shrubs	To be Selected by Owner, See Landscape Plan	
8 Perennial Flowers	To be Selected by Owner, See Landscape Plan	
Cleaning		
	House cleaned prior to closing, including washing of windows	
Warranty		
	Sterling Homes Properties LLC Warranty as per contract	
	Continuing a policy of constant research and improvement, Sterling Homes Properties LLC reserves the	
	right to make substitutions and specification changes.	
		1



#### **HOME - CONSTRUCTION SPECIFICATIONS**

Harvey Slimline All Vinyl Windows, Double insulated, Low E, GBG Grills 6 over 0 6 9/16 primed interior jambs, 2 1/2 colonial case interior

J Channel Only (Brickmould)

EZ-Tilt cleaning

Screens included

Energy Star Qualified Maximum U Factor 0.30

Letter Size Quantity Description Location Image Notes Living Room, Dining A 35x65 5 Double Hung Room  $\hat{\mathbf{U}}$ Ð Owners Bedroom, в 34x53 8 Double Hung Bedroom 2 & 3  $\hat{\mathbb{C}}$ ₽ С 34x41 1 Double Hung Powder Room Û M D 34x49 1 Double Hung Owner Bath  $\hat{\mathbf{U}}$ ₽ Е 42x49 1 Double Hung Kitchen Û F 30x30 1 Awning Stair Landing G 34x34 2 Awning Living Room î1 ΠĪ EG 55x48 1 Egress Lower Level \_\_\_\_\_\_\_



#### **HOME - CONSTRUCTION SPECIFICATIONS**

EXTERIOR DOORS

Therma-Tru Smooth Star Fiberglass Exterior Doors with full weather stripping and adjustable sills

6 9/16 primed jambs

5/4 x 4 flat exterior case, Double bore set-up

EZ Set Satin Nickel knob and deadbolt hardware, All doors keyed alike

	Quantity	re, All doors keyed alike Description	Opens	Size	Туре	Hardware	Image	Notes
Foyer Entry								
	1	S601 with S210SL Sidelite	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Garage - Mudroom	Entry	1	1	1				1
	1	S220 2 Panel <b>6'-6"</b> height	RH	3'-0" <b>6'-6"</b>	2 Panel	Double Bore		
Dining to Future Decl	<	1	I	1	11			.1
	1	S118	RH	3'-0" 6'-8"	Full Glass	Double Bore		
Exterior Door Hardwa	are	1						
Knobs	3	EZ - Set Keyed Entry w/deadbolt				Satin Nickel		All Keyed Alike
		rd, 4 9/16 PFJ split jambs		ITERIOR DOORS			-	
Colonial Casing both sic EZ-Set Satin Nickel Har Ball catches and (2) Du Interior Doors	dware	luded	1	1	1			
	13	Masonite Smooth	See Plans - will display more clearly with plans	TBD	2 Panel Hollow Core	Double Bore		
	2	Masonite Smooth	See Plans - will display more clearly with plans	TBD	Double Doors	Double Bore		Pantry, Bedroom #3
Door to Future Bonus Room	1	Masonite Smooth	RH	TBD	Solid Core	Double Bore		with Threshold Weather Stripping
Interior Door Hardwa	ire						· • •	
Knobs	14	EZ - Set				Satin Nickel		
Knobs	4	EZ - Set				Satin Nickel		Dummy for Ball Latch Double Doors
Hinge Bumps	18					Satin Nickel		



HOME - CONSTRUCTION SPECIFICATIONS									
	Quantity	Description	SKU	ltem	Color	Image Notes			
Garage Exterior		· ·							
	1	One Light Outdoor Wall Lantern	534299	Maxim 1024PE	Pewter				
Deck Exterior	Deck Exterior								
	1	One Light Outdoor Wall Lantern	967425	Maxim 1025PE	Pewter				
Front Porch									
	2	LED Flush Mount	62-1801	Satco	White				
Foyer		1			1				
	1	Three Light Semi Flush Mount	738584	Kichler 43669NI	Brushed Nickel				
Mudroom Hall									
	3	LED Flush Mount	62-1801	Satco	White				
Kitchen Island	1	1		1		1			
	2	One Light Mini Pendant	738588	Kichler 43668NI	Brushed Nickel				
Kitchen						1			
	5	LED Flush Mount	62-1801	Satco	White				
Kitchen Sink									
	1	LED Flush Mount	62-1801	Satco	White				



Dining Room							
	1	Five Light Chandelier	738590	Kichler 43665NI	Brushed Nickel	teres	
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel		
Powder		1			1		
	1	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		Pointed Down
Stairwells							
	2	One Light Wall Sconce	738960	Kichler 45568NI	Brushed Nickel	(j)	1 - Main to Second Floor and 1 - in Main to Lower Level
Upstairs Hall		1			1		
	3	LED Flush Mount	62-1801	Satco	White		
Owners Bedroom							
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel		
Owners Vanity					-		
	2	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		Pointed Down
Owners Closet						1	
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel		



Bedroom #2								
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel			
Bedroom #2 Closet	Bedroom #2 Closet							
	1	LED Ceiling Wrap	177424	Nuvo Lighting 65-1081	White			
Bedroom #3								
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel			
Bath #2				-	-	-		
	1	Three Light Bath	738938	Kichler 45570NI	Brushed Nickel		Pointed Down	
Other		ı		·	·	·	·	
Garage, Future Bonus Room, Lower Level	12	PC Lights					Supplied by Electrician	



HOME - CONSTRUCTION SPECIFICATIONS									
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes		
Sink	1	32" Undermount 16 Gauge Stainless Steel Double Bowl Kitchen Sink	Krauss	KBU32	Stainless Steel		32" L x 18" W, 8.5"D (2) Strainers and Grates		
Faucet	1	Arbor Single-Handle Pull- Down Sprayer	Moen	7594C	Chrome				
Owner's Bath									
Faucet	2	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	The			
Shower	1	ENSEMBLE™ CURVE 60" x 34" Vikrell® shower, center drain	Sterling	72230100-0	White		Straight Curtain Rod Installed.		
Shower Fixture	1	Eva Collection Eco- Performance Trim Kit	Moen	T2138EP	Chrome	<ul> <li>Solution</li> </ul>	Moen 2520 Shower Valve		
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height		



Bath #2							
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	The	
Tub/Shower	1	60-1/4" x 32" Curve Bath/Shower with LH Drain	Sterling	71220110-0	White		Straight Curtain Rod Installed.
Tub/Shower Trim	1	Eva Conversion Eco- Performance Tub/Shower Trim	Moen	T2139EP	Chrome	T O S	Moen 2520 Shower Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height
Powder Bath					1	1	
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	The	
Pedestal Sink	1	Edgemere Pedestal Sink	American Standard	0445.400	White	Ť	
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height



		HOME -	CONSTRUCTIO	ON SPECIFICA	TIONS		
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes
Kitchen Surround							
Knob	18	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel	9	
Kitchen Island							
Knob	4	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel	9	
Owner's Bath	1			1	1	1	
Knob	7	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel	9	
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome		
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome	E.	
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome		
Powder Room							
Towel Ring	1	Eva Bathroom Hand Towel Ring	Moen	YB2886CH	Chrome	S	
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome	S.	
Bath #2							
Knob	5	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel		
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome	R.	
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome	E.	
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome		

#### **HOME - CONSTRUCTION SPECIFICATIONS**

			WOO	D			
	Make	Style	Finish	Size		Image	
Foyer, Hallway, Kitchen, Dining Room	Lauzon	Expert	TBD	TBD		-	Height 3/4"
			TILE				
Location	Make/Style	Finish/Color	Tile Size	Orientation	Tile Grout	Image	Notes
Owner's Bath	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Transitions to Dreamweaver Carpet
Mudroom	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to 3/4" Wood.
Powder	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to Mudroom Tile.
			VINY	L			
Location	Make	Style	Color			Image	Notes
Bath #2	Tarkett	Fresh Start	TBD	TBD	TBD		Transitions to Dreamweaver Carpet



CARPET								
Location	Make	Style	Color	Details		Image		
Owner's Bedroom, Owners WIC	Dreamweaver	Pinpoint	TBD				Transitions to Owners Bath Tile.	
Bedroom 2, Bedroom 3	Dreamweaver	Pinpoint	TBD				Transitions to Dreamweaver Carpet.	
Upstairs Hall, Staircase to Second Floor	Dreamweaver	Pinpoint	TBD				Transitions to 3/4" Wood.	



		НОМ	E - CONSTRUCTIO	ON SPECIFICA	ATIONS		
Appliance	Quantity	Manufacturer	Model	Color	Description	Image	Notes
Refrigerator	1	GE	GNE27JYMFS	Stainless	GE Energy Star 27.0 Cu. Ft. French Door	1	Fingerprint Resistan Door
Gas Range	1	GE	JGB735SPSS	Stainless	GE 30" Free Standing Gas Convection Range		
Dishwasher	1	GE	GDT550PYRFS	Stainless	GE Dishwasher with Top Controls	-	
Microwave	1	GE	JVM3160RFSS	Stainless	GE 1.6 Cu. Ft. Over- the-Range- Microwave Oven		
Washer							Available as option
Electric Dryer							Available as opti