

KOUSA PLAN - CONSTRUCTION SPECIFICATIONS

Sterling Dogwood Circle LLC 1037 Hinesburg Road, Suite A South Burlington, VT 05403 Homeowner/Project

DWC # Milton, VT 05468 Specification Date: 4/28/25

Site Plan Date: Plan Date: 4/14/25 Electric Plan: 4/14/25

Kousa Plan: One story home with unfinished lower level. Approximately 1,356 square feet of living space; 1,356 square feet of unfinished Lower Level, 400 square foot 2-car garage, and a 50 square foot front porch.

Location Total Square Feet
First Floor 1,356

Total Finished Square Feet 1,356
Lower Level 1,356

Garage 400 Front Porch 50

Personal Choice Lists PCL# Date **Color Code GRAPE ORANGE** GREEN BLUE **PURPLE** PINK HUNTER **SKY BLUE** LAVENDER **BROWN** NAVY **CRANBERRY AQUA PEACH** RED

Specification and Appendix Approval

Appendix A: Window Schedule
Appendix B: Exterior and Interior Door Schedule
Appendix C: Lighting Schedule
Appendix D: Plumbing Schedule
Appendix E: Finish Hardware Schedule
Appendix F: Flooring Schedule
Appendix G: Appliance Schedule

Client		Date
Client		Data
Liient		Date
Builder	Collin H. Frisbie	Date



	KOUSA PLAN - CONSTRUCTION SPECIFICATIONS	
Section	Information	Image
Permits		
	Builder responsible to obtain all necessary permits including:	
	- Soil Erosion and Sediment Control	
	- Zoning	
Surveys		
	Home is to be staked by builder	
Site Clearing	, , , , , , , , , , , , , , , , , , ,	
Site cicumg	Builder is responsible for all site clearing, as needed	
Utilities Connections	bullet 13 responsible for all site clearing, as needed	
	Builder responsible for all site work and site balance to include	
Water	Connection to City of Milton water system	
Sewer	Connection to City of Milton sewer system	
Gas	Connection to Vermont Gas lines at road.	
Power	Underground power, 2-1/2" conduit to home	
Cable	2" Cable TV conduit to home	
Future Phone	2" Future Phone conduit to home	
i uture i none	All excavation, fill and labor is included	
inergy Package	riii excavation, nii ana labor is included	
	Home to be built to VT Residential Building Energy Standards (RBES)	
Home to Include	Home to be built to VI Residential building Energy Standards (RbL3)	
nome to miciate	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
	Vented to the outside	
	Additional caulking and air sealing of joists to reduce air infiltration into the home, including shoe	
	plate; windows; and where wires and pipes go to cold spaces	
	R-15 Rigid Thermax insulation on Interior of Lower Level - floor to top of concrete wall	
	Selected use of closed cell foam to improve overall air sealing of attic in home	
	Blower Door Test as home completed required for VT RBES	
Color Drop	Home solar ready with 1-1/2" Conduit running from LL up to Attic Space	
Solar Prep Foundation	Home solar ready with 1-1/2 Conduit running from LL up to Attic Space	
	Poured Concrete	
Type Form	+/-8'	
Wall Height	+/-8 +/-6'10" Wall Exterior / +/-6'-6" Wall Interior	
Lookout Height	4' Frost Wall	
Strength	Min. 3000 PSI @2 days with steel reinforcement	
Footer	Continuous 8" x 16" reinforced	
lat Work Concrete	CONTINUOUS O X TO TENNOTICEU	
Lower Level	Poured Concrete	
Finish	Smooth	
"Keyway" Joints	Saw cut	
Thickness	Saw cut Δ"	
Strength	House: Min. 3000 PSI @ 28 days Garage: Min. 4000 PSI @ 28 days	
Sueligui		
Moisture Barrier	Tarred damp proofing membrane sprayed on exterior of foundation walls.	
	6 mil poly under concrete house slab.	
	Footing drains installed at base of footers around Lower Level exterior and interior of home, run	
Ground water controls	to a HSB1822 sump with Zoeller M53 cast iron submersible sump pump. Drain tile buried in clean	
	stone; covered with mirafi fabric; clean sand fill against foundation. Site graded to shed surface	
	water away from house.	
Lower Level Slab Plumb	Available as an Option	



		HOMES
Driveway/Entrance		
Drive	12" thick gravel two car driveway on top of mirafi fabric.	
Dilve	Driveway to be finish paved with 2" of compacted asphalt.	
Walkway	+-42" Sidewalk from front porch to driveway will be Brussels Block, Color is Limestone.	
Frame		
Exterior Walls	2x6 SPF 24" o.c.	
Interior Walls	2x4 SPF 24" o.c.	
Diata Haight	9'-1" on first floor and +/-7'-7.5" in lower level	
Plate Height	Framed +/-12" Foundation Wall	
Plate	2x6 treated southern yellow pine with foam sill seal	
Floor Framing	2x10 SPF 19.2" o.c.	
Sub Flooring	3/4" 4x8 T&G OSB glued and nailed	
Cindon.	2 or 3 ply 2x12, nailed and glued, as specified by engineering load design, supported by 3-1/2"	
Girders	concrete filled lally columns in Lower Level	
Sheathing	7/16" 4x8 OSB	
Roof	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting	
Roof Pitch	Pitches: 7/12 at Main House; 12/12 at Garage; 6/12 at Front Porch	
House Wrap	Professional house wrap with flashing around all windows and doors	
Roofing		
	Ice and water shield on eaves and valleys. Vented on ridge to achieve proper ventilation.	*************************************
Underlayment	Owens Corning ProArmor Synthetic Roof Underlayment	
Shingles	Owens Corning TruDefinition Shingles Limited Lifetime Warranty	
Color	Slatestone Gray	
Siding/Exterior Elements		
Siding	Norandex Woodsman Select	
Gable Ends	Double 4" Color to selected by owner	
Clapboard	Double 4", Color to be selected by owner	
Board and Baton	None	
Eaves	Two piece aluminum wrapped - White	
Soffit	Perforated soffit for proper venting	
Corners	6" White Vinyl Corners with Foam Backer	
Trim Details	Frieze board and Garage Door Trim to be PVC	
Drip Edge	Galvanized	
Shutters	Available as Option	
Gutters & Downspouts		
Gutters & Downspouts	White Seamless Gutters	
Windows		
	See Appendix A: Window Schedule	
Brand	Harvey Slimline	
Color	White	
Construction	Vinyl, Low-E, Insulated Double-Pane	
Exterior Casing	J Channel Only (Brickmould)	
U-Factor	0.29	
Grills	Grills Between Glass 4 over 0	
Screens	Fiberglass Mesh	
Exterior Doors		
	See Appendix B: Exterior and Interior Door Schedule	
Brand	Therma-Tru	
Color	See Exterior Paint Section	
Construction	Insulated Fiberglass	
Exterior Casing	5/4x4 Flat Hybrid Casing and Rot Resistant Jamb	
Storm Doors	None	



Overhead Garage Doors		
Model	8300 Series Insulated Steel Door	
Size	16' x 7'	
Design	Long Panel	
Glass	Available as an Option	
Color	Manufacturer White	
Opener	8" lift master 1/2 horsepower electric opener	
Remotes	2 remotes included	
Frame Key Pad	Keyless entry punch pad mounted at +/-54" above slab	
Decks & Porches		
Covered Entry Porch		
Porch Framing	5' x 10' framed with PT 2x8 joists	
Decking	5/4x6 PT decking	
Posts	PVC wrapped and PT 6x6 Posts, 2x8 roof beams - White. Posts wrapped top and bottom.	
Roof	Roof to be truss framed, roof shingles to match house	
Ceiling	White vinyl bead board	
Stairs	Stairs from porch to walkway to be PT box steps with 5/4x6 14" PT treads.	
Rail	Available as an Option	
Finish	Porch posts, beams - White CPVC Trim	
	Porch decking, stair tread, risers and PT Rim stained with Total Wood Preservative - Selected by	
Color	Owner	
Exterior Paint		
Exterior Doors - Excluding Front Door	Painted Satin Finish, White	
Exterior Trim - Including Frieze Board	Turred Sum Finish, Write	
and Door Surrounds	Painted Satin Finish, White	
Front Door	2 coats Exterior Paint, Color to be Selected by Owner	
Sidelight	2 coats Exterior Paint, Color to be Selected by Owner	
Front Porch Rail	Available as an Option	
Front Porch Posts	CPVC Wrapped, White	
Front Porch Roof Beams	CPVC Trim, White	
Front Porch Rim board	Stained. Color to be Selected by Owner.	
Front Porch Stair Risers	Stained. Color to be Selected by Owner.	
Front Porch Decking	Stained. Color to be Selected by Owner.	
Electrical & Low Voltage	Stanted Color to acconduct by Chines	
	Underground electrical service, 40 circuit 200 AMP Panel with Surge Protection.	
	Open double slot for future solar.	
Plugs and Switches	ppen addition to take some	
Switch Style	Toggle	a a
Plate Style	Toggle screw on plates	
Switch Color	White	F
Dimmers	Available as Option	
Exterior Plugs	Per Electrical Plan	Φ
Lighting		
Lighting Fixtures	See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	
Under Cabinet Lighting	Available as Option	
Miscellaneous	·	
	GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished	
Outlets	areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.	1
Door Chime	Nutone BK125LWH: One 2-note, white door chime	
	1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (2 Total) - First Alert 10 Year Sealed Battery	- 1111
Smoke/CO	Smoke Alarm Model SM110V-AC	0
Bath Fans	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM	
Paddle Fan Boxes	Paddle fan rated boxes in all Bedrooms, Dining room, and Living room	
Cat 6 (data/phone)	Yes, per electrical plan	
Coax Cable	Yes, per electrical plan	
Dryer	220 Outlet for Future Electric Dryer	
Solar Prep	1-1/2" Conduit running from LL up to Attic Space	
Future EV Garage Heat Sensor	Available as Option	
Garbage Disposal	Available as Option	
Gui buge Disposai	reduced of option	



Light Fixtures		
	See Appendix C: Light Fixture Schedule	
	Plumbing	
Heating and Venting		
Furnace	Ducane - 97GUH045BV12	
Furnace Size	45,000 BTU with ECM Blower	
Efficiency Rating	96%	
Zones	Zone 1: First Floor	
Second Zone	Available as Option	[PRO]
HRV	Broan B160H65RT HRV with VTTOUCHW wall control	
Air Conditioner	Available as Option	A14
Thermostat	PurePro - Located on First Floor, See Elec Plans	
Bath Venting	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
Batti Venting	Vented to the outside	
Dryer Venting	Vented to the outside	
Microwave/Range Hood Venting	Vented to the outside	
Gas		
Main Kitchen Range	Yes	
Main Fireplace	Available as Option	
Dryer	No, Electric	
Furnace	Yes	
Hot Water System	Yes, State GS650YRT Gas water heater	
Fireplace and Mantle		
Fireplace in Living Room	Available as Option	
Plumbing Fixtures		
	See Appendix D: Plumbing Schedule	
Miscellaneous Plumbing		
Outdoor Faucets	2 Frost-Free Hose Bibs, located at back of the main house and on the side of the front porch	
Hot Water Heater	State GS650YRT Gas water heater	
Laundry	Washer Box Valve with single handle shutoff and drain; appliances pricing optional	
	PVC Drainage plumbing.	
Plumbing	PEX continuous piping for all domestic water.	
	All plumbing installed according to National Plumbing Code by licensed plumber.	
Radon	3" Radon Piping runs from under Lower Level concrete slab through roof.	
Kauon	This is a passive system, no fan. Pipe labelled in attic space.	
Utility Sink	Available as Option	



	Cabinets & Countertops	HOWE3
Cabinets	Cabinets & Countertops	
Kitchen		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color		
Kitchen Island	Color to be determined by Owner	
Brand	Fahrunged Calaus/Allura Carias	
	Fabuwood Galaxy/Allure Series	
Style Color	Full Overlay Doors	
	Color to be determined by Owner	
Owner's Bath	73 \(\sigma = \frac{1}{2} \sigma = \sigma \frac{1}{2} \s	
Size	72" Vanity with 2 bowls	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Bath #2		
Size	60" Vanity with single bowl	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Countertops		
Kitchen		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	In 1111
Cut-Outs	Under Mount Sink	
Backsplash	4" Classic Series Quartz	
B/S Location	Perimeter Back Only	
Kitchen Island		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	
Cut-Outs	None	Kitchen Tops (not color or Style)
Owner's Bath		
Style	Cultured Marble with 2 integrated flush rectangle bowls	7
Color	Cotton White	Ma
Edge Detail	Square Edge	AU
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
Bath #2		
Style	Cultured Marble with 1 integrated flush rectangle bowl	
Color	Cotton White	
Edge Detail	Square Edge	
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
D/O LOCATION	15000 5007	l .



R-21 5-1/2" Timberfill Dense Pack insulation	
R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing at Bathrooms and Laundry)	TimberFill
Box sill in first and second floor joists insulated with 3" foam R-21 rim insulated	ALC:
18" R-60 Timberfill with backer boards at eves for ventilation	
Not insulated	
2-1/2" R-15 Thermax glued to concrete wall	
1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings	
Smooth Finish, minor shadow variations are possible in ceilings	
Walls and Ceiling - 5/8" Sheet Rock, Fire Coat, and Primed	
	4
·	
· · · · · ·	4
Available as Option	
Cubbies and Bench at Mudroom	
Black Metal Hooks at Mudroom	
Plate Glass mirror with ground edge, no bevel	
Plate Glass mirror with ground edge, no bevel	AEU
Carpet Grade Stairs	
First Floor half wall with a hardwood cap and railing on wall. Cap to Match First Floor flooring.	
Rail on wall to Match First Floor Flooring	
-	
	!
All closets systems will be vented wire and the system is indicated on the plan. See Closet Plan for Details.	
	·
1 coat primer	
None	1
To match walls	1
Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	1
Color to be Benjamin Moore OC-149 Decorator's White	
Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	1
Color to be Benjamin Moore OC-149 Decorator's White	Decorator's White
Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	OC-149
	30 117
Color to be Benjamin Moore OC-149 Decorator's White	
Color to be Benjamin Moore OC-149 Decorator's White Stained half wall cap and railing to Match Wood on First Floor	-
	R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing at Bathrooms and Laundry) Box sill in first and second floor joists insulated with 3" foam R-21 rim insulated 18" R-60 Timberfill with backer boards at eves for ventilation Not insulated 2-1/2" R-15 Thermax glued to concrete wall 1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings Smooth Finish, minor shadow variations are possible in ceilings Walls and Ceiling - 5/8" Sheet Rock, Fire Coat, and Primed 2-1/2" Colonial Casing 3-1/2" Colonial Base Board 4-60" High Wainscot at Mudroom under Black Metal Coat Hooks Available as Option Cubbies and Bench at Mudroom Black Metal Hooks at Mudroom Plate Glass mirror with ground edge, no bevel Plate Glass mirror with ground edge, no bevel Carpet Grade Stairs First Floor half wall with a hardwood cap and railing on wall. Cap to Match First Floor flooring. Rail on wall to Match First Floor Flooring Satin Nickel All closets systems will be vented wire and the system is indicated on the plan. See Closet Plan for Details. 1 coat primer 2 coats Low VOC Flat Latex Paint, Color to be selected by owner, OK to Color Match None To match walls Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint, Color to be Benjamin Moore OC-149 Decorator's White Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint, Color to be Benjamin Moore OC-149 Decorator's White



Interior Doors		
	See Door Appendix B: Exterior and Interior Door Schedule	
Finish Hardware		
	See Appendix E: Finish Hardware Schedule	
Flooring		
	See Appendix F: Flooring Schedule	
Appliances		
	See Appendix G: Appliance Schedule	
Landscaping		
	All disturbed portions of yard to be seeded.	
Lawn	Lawn area will generally include front yard, side yard and rear yard.	
	Lawn area to be covered with approximately 4" of native topsoil.	
Street Trees	One Tree, per permit. Tree to be maintained by Homeowner.	
6 Foundation Shrubs	See Landscape Plan	
6 Perennial Flowers	See Landscape Plan	
Cleaning		
	House cleaned prior to closing, including washing of windows	
Warranty		
	Sterling Dogwood Circle LLC Warranty as per contract	
	Continuing a policy of constant research and improvement, Sterling Dogwood Circle LLC	
	reserves the right to make substitutions and specification changes.	



KOUSA PLAN - CONSTRUCTION SPECIFICATIONS

Harvey Slimline All Vinyl Windows, Double insulated, Low E, GBG Grills 4 over 0 6 9/16 primed interior jambs, 2 1/2 colonial case interior

J Channel Only (Brickmould)

EZ-Tilt cleaning

Screens included

Energy Star Qualified

Maximum U Factor 0.29

Letter	Size	Quantity	Description	Location	lmage	Notes
А	40x65	8	Double Hung	Den/Bedroom, Dining Room, Living Room, Owner's Bedroom		
С	40x42	2	Double Hung	Owner's Bath, Bath #2		
К	42x49	1	Double Hung	Kitchen		
1F	40x30	1	Fixed	Den/Bedroom		
EG	55x48	1	Egress	Lower Level		Additional as Optional
G	36x18	1	Vinyl	Lower Level		



KOUSA PLAN - CONSTRUCTION SPECIFICATIONS EXTERIOR DOORS

 $Therma-Tru\ Smooth\ Star\ Fiberglass\ Exterior\ Doors\ with\ full\ weather\ stripping\ and\ adjustable\ sills\ 6\ 9/16\ primed\ jambs$

5/4 x 4 flat, Hybrid Rot Resistant Case & Jamb, Double bore set-up

Dexter Stratus Satin Nickel knob and deadbolt hardware, All doors keyed alike

	Quantity	Description	Opens	Size	Туре	Hardware	Image	Notes
Foyer Entry								
	1	S220 w/12" S100SL full glass sidelight	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Garage - Mudro	om Entry							
	1	S220 2 Panel	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Dining Room Ent	ry from Optional Dec	k						
	1	S118	RH	3'-0" 6'-8"	Full Glass	Double Bore		
Exterior Door Ha	dware							
Knobs	3	Dexter Stratus Keyed Entry w/deadbolt				Satin Nickel	F A	All Keyed Alike
				INTERIOR DO	ORS			
Colonial Casing bo Dexter Stratus Sa		nardboard, 4 9/16 PFJ pair included	split jambs					
Interior Doors								
	10	Masonite Smooth	See Plans - will display more clearly with plans	TBD	2 Panel Hollow Core			
Interior Door Har	dware							
Knobs	10	Dexter Stratus				Satin Nickel		
Hinge Bumps	10					Satin Nickel		



	HOMES						
	KOUSA PLAN - CONSTRUCTION SPECIFICATIONS						
	Quantity	Description	SKU	Item	Color	Image	Notes
Garage Exterior							
	1	TBD					
Dining Room Exterio	r						
	1	TBD					
Front Porch				I			
	2	TBD					
Foyer						1	
	1	TBD					
Mudroom/Front Hall							
	3	TBD					
Den/Bedroom #2							
	1	TBD					
Kitchen Island							
	2	TBD					
Kitchen Ceiling							
	3	TBD					
	J						
Kitchen Sink							
	1	TBD					
	1	ופט					
Dining Pages							
Dining Room							
	_						
	1	TBD					
ausa Dlan			11 of				0/25/20



				НС	MES
Living Room					
	1	TBD			
Stairwell					
	1	TBD			
Laundry					
	1	TBD			
Owner's Hall					
	1	TBD			
Owners Bedroom Ho	all				
	1	TBD			
Owners Bedroom					
	1	TBD			
Owners Vanity					
	2	TBD			
Owners Closet					
	1	TBD			
Other					
Garage, Lower Level	10	PC Lights			Supplied by Electrician



						н	OMES	
KOUSA PLAN - CONSTRUCTION SPECIFICATIONS								
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes	
Sink	1	32" Undermount 16 Gauge Stainless Steel Double Bowl Kitchen Sink	Krauss	KBU32	Stainless Steel		32" L x 18" W, 8.5" (2) Strainers and Grates	
Faucet	1	Arbor Single-Handle Pull- Down Sprayer	Moen	7594C	Chrome			
Owner's Bath								
Faucet	2	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	70		
Shower	1	Medley® 60" x 34" Vikrell® shower, center drain	Sterling	72430100-0	White		Straight Curtain Roo Installed.	
Shower Fixture	1	Eva Chrome Posi-Temp® Shower only	Moen	T2132	Chrome	6	Moen 2520 Showe Valve	
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Heigh	



Bath #2								
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	71		
Tub/Shower	1	Ensemble™ Medley® 60" x 32" Vikrell® bath/shower, right drain	Sterling	71320120-0	White		Straight Curtain Rod Installed.	
Tub/Shower Trim	1	Eva Chrome Posi-Temp® Tub/Shower	Moen	T2133	Chrome		Moen 2520 Shower Valve	
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height	



						H	OMES
		KOUSA PLAN	N - CONSTRUC	CTION SPECIF	ICATIONS		
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes
itchen Surround							
Knob	18	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel		
itchen Island							
Knob	4	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel		
Owner's Bath							
Knob	7	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel		
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome		
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome		
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome	3	
ath #2							
Knob	5	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel		
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome		
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome	2	
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome		



KOUSA PLAN - CONSTRUCTION SPECIFICATIONS

WOOD								
	Make	Style	Color	Size		Image		
		<u> </u>	00.0.	<u> </u>		, ge		
Foyer, Hallway, Kitchen, Dining Room, Living Room	Hallmark	Novella	Hemingway Oak	6" x 6'-2"			7/16" Thick	
Location	Make/Style	Finish/Color	Tile Size	Orientation	Tile Grout	Image	Notes	
Locuion	make/style	Tillisti, Color	THE SIZE	Onemanon	THE GIGGI	image	Notes	
Owner's Bath	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Transitions to Dreamweaver Carpet.	
Mudroom	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to 7/16" Wood.	
			VINY	'L				
Location	Make	Style	Color			Image		
Bath #2	Tarkett	Fresh Start	TBD	TBD			Standard Underlayment. Transitions to 7/16" Wood.	
Laundry	Tarkett	Fresh Start	TBD	TBD			Standard Underlayment. Transitions to 7/16" Wood.	
			CARP	ET				
Location	Make	Style	Color	Details		Image		
Owner's Bedroom, Owners WIC	Dreamweaver	Pinpoint	TBD				Transitions to Owners Bath Tile & Transitions to 7/16" Wood.	
Den/Bedroom	Dreamweaver	Pinpoint	TBD				Standard Underlayment. Transitions to 7/16" Wood.	



						H	OMES
		KOUSA PI	.AN - CONSTRU	CTION SPECI	IFICATIONS		
Appliance	Quantity	Manufacturer	Model	Color	Description	Image	Notes
							<u>'</u>
Refrigerator	1	GE	GNE27JYMFS	Stainless	GE Energy Star 27.0 Cu. Ft. French Door		Fingerprint Resistant Door
Gas Range	1	GE	GGF600AVSS	Stainless	GE® 30" Free- Standing Gas Convection Range with No Preheat Air Fry and EasyWash™ Oven Tray		
Dishwasher	1	GE	GDT550PYRFS	Stainless	GE Dishwasher with Top Controls	•	
Microwave	1	GE	JVM3160RFSS	Stainless	GE 1.6 Cu. Ft. Over- the-Range- Microwave Oven		
Washer							Available as option
Electric Dryer							Available as option